

Suitability table of the

SAVIO, SAVIO by Pininfarina and LUIGISAVIO

accessories to profile series of

PURSO OY - FINLAND

LK73 - LK 73 DOOR - P50 - P50 DOOR

NSAVIO
by
pininfarina

1 LUIGISAVIO

NSAVIO

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	870.1	MANON (patented) Handle for casement in die-cast metal or brass, dist. between centres 84.5-98 mm, 2 socket head cap screws M5x14 in black galvanized steel (for C and OTT finishes 2 socket head cap screws M5x10). PVD X, PVD H and OTT finishes packaging 5 pcs.; C finish: packaging 50 pcs.	20	1013, 1015, 1247, 6002, 6005, 7016, 7032, 7035, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, GREY, OTT, PVD H, PVD X, RD501, SILV, WT005	●		●	
	870.2	MANON Like 870.1 but with dist. between centres of 92-104 mm.	20	1013, 1015, 6002, 6005, 7032, 7035, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR50, GR51, GR606, OTT, PVD H, PVD X, RD501, SILV, WT005	●		●	
	870.753	MANON (patented) Handle for casement in die-cast metal or brass, with safety cylinder (same keys), dist. between centres 84.5-98 mm, 2 socket head cap screws M5x14 in black galvanized steel (OTT: 2 socket head cap screws M5x10). OTT finishes packaging 5 pcs.; C finish: packaging 50 pcs.	10	1013, 1015, 6002, 6005, 7032, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BW21, C, GR217, GREY, OTT, SILV	●		●	
	870.754	MANON Like 870.754 but with dist. between centres of 92-104 mm.	10	1013, 1015, 6002, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, OTT, PVD H, PVD X, SILV, WT005	●		●	
	870.755	MANON (patented) Handle for casement in die-cast metal, without grip handle (grip handle art.1243.599), dist. between centres 84.5-98 mm, 2 socket head cap screws M5x14 in black galvanized steel.	10	1013, 8019, 9001, 9005, 9010, B.SA, BL10, BW21, GR217, SILV	●		●	
	870.756	MANON Like 870.755 but with dist. between centres of 92-104 mm.	10	1013, 7035, 8019, 9005, 9010, GR217, PVD X, SILV	●		●	
	872	MANON (patented) Handle made of die-cast metal, dist. between centres 130 mm, 2 plates and 2 cap screws M4x12 in black galvanized steel.	20	1013, 1015, 8017, 8019, 9001, 9005, 9010, BL10, BR5, BR801, C, GR217, GR606, RD501, SILV, WT005	●		●	
	872.751	MANON (patented) Handle made of die-cast metal, with security cylinder (same keys), dist. between centres 130 mm, 2 plates and 2 cap screws M4x12 in black galvanized steel.	10	1013, 1015, 7035, 8017, 8019, 9001, 9005, 9010, BR5, SILV	●		●	
	872.752	MANON (patented) Handle made of die-cast metal, without grip handle (grip handle art.1243.599), dist. between centres 130 mm, 2 plates and 2 cap screws M4x12 in black galvanized steel (C finish: packaging 50 pcs.).	10	9005, C	●		●	

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	873.1	MANON (patented) Handle for tilt and turn in die-cast metal or brass, dist. between centres 84.5-98 mm, 2 screws socket head cap M5x14 in stainless steel 304 (C: packaging 50 pcs.).	5	1013, 1015, 1247, 3001, 6002, 6005, 7016, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR51, GR606, GREY, OTT, PVD H, PVD X, RD501, SILV, WT005	●		●	
	873.2	MANON Like 873.1 but with dist. between centres of 92-104 mm.	5	1013, 1015, 6002, 6005, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BL25, BR5, BR801, BW21, C, GR217, GR50, GR51, GR606, OTT, PVD H, PVD X, RD501, SILV, WT005	●		●	
	873.753	MANON (patented) Handle for tilt and turn in die-cast metal or brass, with safety cylinder (same keys), dist. between centres 84.5-98 mm, 2 socket head cap screws M5x14 in stainless steel 304.	5	1013, 1015, 6002, 6005, 7032, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BW21, C, GR217, OTT, PVD H, PVD X, SILV	●		●	
	873.754	MANON Like 873.753 but with dist. between centres of 92-104 mm.	5	1013, 1015, 6002, 7032, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BW21, C, OTT, PVD H, PVD X, SILV	●		●	
	873.755	MANON (patented) Handle for tilt and turn in die-cast metal, without grip handle (grip handle art.1243.599), dist. between centres 84.5-98 mm, 2 socket head cap screws M5x14 in stainless steel 304.	5	1013, 8019, 9005, 9010, GR217, SILV	●		●	
	873.756	MANON Like 873.755 but with dist. between centres of 92-104 mm.	5	1013, 8019, 9005, 9010, BL10, C, SILV	●		●	
	873.771	MANON (patented) Left handle for tilt and turn tilt-first function in die-cast metal or brass, with safety cylinder (same keys), dist. between centres 84.5-98 mm, 2 socket head cap screws M5x14 in stainless steel 304.	5	1013, 7032, 7035, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, OTT, PVD X, SILV	●		●	
	873.772	MANON Like 873.771 but right handle.	5	1013, 7032, 7035, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, GR217, OTT, PVD X, SILV	●		●	
	873.773	MANON Like 873.771 but with dist. between centres of 92-104 mm.	5	1013, 8019, 9001, 9005, 9010, 9016, BL10, GR217, OTT, PVD H, PVD X, SILV	●		●	
	873.774	MANON Like 873.773 but right handle.	5	1013, 8019, 9001, 9005, 9010, 9016, BL10, BR5, GR217, OTT, PVD H, PVD X, SILV	●		●	
	874.1	MANON (pat.) Handle with handle in nylon or in brass, distance between centres of 43 mm, 8 mm square spindle and 2 cap screws M5x35 in galvanized steel (to combine with art. 1200/8, 1201/8, 1203/8 and 1204/8).	5	.74, .75/A, .78/B, OTT	●		●	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	874.2	MANON (pat.) Handle base with extractable grip made of die-cast aluminium and nylon base of the same colour of the handle, distance between centre of 43 mm, 8 mm square spindle, 2 galvanized steel cap screws M5x30 and 1 key for handle removal made of galvanized steel; dimension 10x1 mm (1 piece each box). To combine with art. 1200/8, 1201/8, 1203/8 and 1204/8.	5	1013, 3003, 9001, 9005, 9010, B.SA, BL25, C, OTT, PVD X, SILV	●		●	
	874.2/7	MANON Like 874.2 but with 7 mm square spindle.	5	1013, 1015, 8019, 9005, 9010, B.SA, BL10, BR5, C, GREY, PVD H, PVD X, SILV	●		●	
	874.3	MANON (pat.) Handle with handle in die-cast metal, base and cap in zamak, distance between centres of 43 mm, 8 mm square spindle with a projecting part of 24.5 mm and 2 cap screws M5x35 in galvanized steel (to combine with art. 1200/8, 1201/8, 1203/8 and 1204/8).	5	1013, 1015, 8019, 9005, 9010, B.SA, BL10, BR5, C, GR217, GR606, GREY, PVD H, PVD X, SILV	●		●	
	874.3/7	MANON Like 874.3 but with 7 mm square spindle.	5	1013, 1015, 8019, 9005, 9010, B.SA, BL10, BR5, C, GREY, PVD H, PVD X, SILV	●		●	
	874.30	MANON (patented) Non-handed double door handle in nylon, with pre-assembled return spring, 8x120 mm square spindle and 4 cap screws Ø 4,2x19 in galvanized steel.	10	.74, .75, .78		●		●
	874.31	MANON (patented) Non-handed double door handle in die-cast metal, with pre-assembled return spring, 8x120 square spindle and 4 cap screws Ø 4,2x19 in galvanized steel (PVD H and PVD X finishes 4 pcs. each box).	10	1013, 1015, 6005, 7035, 7047, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR50, GR51, GR606, GREY, PVD H, PVD X, RD501, SILV, WT005		●		●
	874.32	MANON (patented) Non-handed single handle with pre-assembled return spring and flat handle in die-cast metal, 8x120 square spindle, 2 cap screws Ø 4,2x19 and 2 cap screws Ø 4,2x13 in galvanized steel.	4	1013, 1015, 1247, 6005, 8019, 9001, 9005, 9010, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR50, GR51, GR606, GREY, PVD H, PVD X, SILV		●		●
	874.91	MANON (patented) Double door handle in solid brass, with return spring, gold-plated handle backplates and escutcheons, 4 cap screws Ø 4,2x19 in galvanized steel.	4	OTT		●		●
	874.899	Square spindle 8x140 mm in galvanized steel for door with thickness from 55 to 70 mm.	50			●		
	875.2	Handle in powder coated zamak, dist. between centres 109 mm, 2 cap screws M5x8 in stainless steel 304.	5	1013, 7035, 8019, 9001, 9005, 9010, SILV	●		●	

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	876	MANON (patented) Handle in die-cast metal for external and internal openings, dist. between centres 104-108 mm, 2 plates, 2 cap screws M4x14, 2 cap screws Ø 3.9x25 and 2 galvanized steel nuts M4 (PVD H, PVD X finishes packaging 5 pcs.).	20	1013, 1015, 6005, 7032, 8017, 8019, 9001, 9005, 9010, B.SA, BL10, BR5, BR801, C, GR217, GR606, PVD H, PVD X, RD501, SILV, WTO05	•		•	
	876.751	MANON (patented) Handle in die-cast metal for external and internal openings, with safety cylinder (same keys), dist. between centres 104-108 mm, 2 subscrew plates, 2 cap screws M4x14, 2 cap screws Ø 3.9x25 and 2 galvanized steel nuts M4.	10	1013, 1015, 6005, 7032, 8017, 8019, 9001, 9005, 9010, B.SA, BL10, BR5, BR801, C, GR217, GR50, GR51, GR606, SILV	•		•	
	879	TURANDOT (patented) Handle in die-cast metal for shutters, for external and internal openings, distance between centres 104-108 mm, 2 subscrew plates, 2 socket head cap screws M4x10 and 2 M4 nuts in galvanized steel (PVD X and PVD H: packaging 5 pcs.; C: packaging 50 pcs.).	20	1013, 1015, 3003, 6005, 8017, 8019, 9001, 9005, 9010, 9016, BL10, BR5, BR801, BW21, C, GR217, GR50, GR51, GR606, PVD H, PVD X, RD501, SILV, WTO05	•		•	
	879.2	TURANDOT (patented) Die-cast metal handle for shutters, for external and internal openings, centre distances 104-108, 2 subscrew plates, 2 socket head cap screws M4x10 and 2 nuts of galvanized steel (PVD X and PVD H: packaging 5 pcs.).	20	1013, 1015, 6005, 7035, 7047, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BL25, BR5, BR801, GR217, GR50, GR51, GR606, PVD H, PVD X, RD501, SILV, WTO05	•		•	
	879.3	TURANDOT (patented) Die-cast metal handle, for shutters, for external and internal openings, flat handle, centre distances 104-108, 2 subscrew plates, 2 socket head cap screws M4x10 and 2 nuts M4 of galvanized steel (PVD X and PVD H: packaging 5 pcs.).	20	1013, 1015, 6005, 8017, 8019, 9001, 9005, 9010, BL10, BR5, BR801, GR217, GR50, GR51, GR606, PVD H, PVD X, RD501, SILV, WTO05	•		•	
	879.751	TURANDOT (patented) Die-cast metal handle for shutters, for external and internal openings, with safety lock, centre distances 104-108, 2 subscrew plates, 2 socket head cap screws M4x10 and 2 nuts M4 made of galvanized steel, 1 key (PVD X and PVD H: packaging 5 pcs.).	10	1013, 1015, 6005, 8017, 8019, 9001, 9005, 9010, BL10, BR5, BR801, GR217, GR50, GR51, GR606, PVD H, PVD X, RD501, SILV, WTO05	•		•	
	880.1	GIOCONDA (patented) Handle in die-cast metal, pinion and racks in galvanized steel, dist. between centres 84,5-98 mm, 2 socket head cap screws M5x10 and 2 subscrew plates in black galvanized steel.	20	1013, 8019, 9001, 9005, 9010, 9016, BL10, BR5, BR801, GR217, GR606, RD501, SILV, WTO05	•		•	
	880.2	GIOCONDA Like 880.1 but with dist. between centres of 92-104 mm.	20	1013, 1015, 8017, 8019, 9001, 9005, 9010, BL10, BR5, BR801, GR217, GR606, RD501, SILV, WTO05	•		•	
	883.1	GIOCONDA (patented) Handle for tilt and turn in die-cast metal, pinion and rack in galvanized steel, dist. between centres 84,5-98 mm, 2 socket head cap screws M5x10 in stainless steel.	5	1013, 8019, 9001, 9005, 9010, BL10, BR5, BR801, GR217, GR606, RD501, SILV, WTO05	•		•	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	883.2	GIOCONDA Like 883.1 but with dist. between centres of 92-104 mm.	5	1013, 1015, 8019, 9001, 9005, 9010, BL10, BR5, BR801, GR217, GR606, RD501, SILV, WT005	●		●	
	884	GIOCONDA (patented) Double door handle with handle and mechanism cover in techno-polymer, mechanism in zamak, square spindle 8x120 mm, 2 spiral spring and 4 cap screws Ø 4,2x19 in galvanized steel.	10	.74, .75, .78, .80, .83		●		●
	909	GENOVA Aluminium and Delrin handle, dist. between centres 130 mm, 2 subscrew plates and 2 cap screws M4x14 in black galvanized steel.	20	1013, 3003, 6005, 8017, 9001, 9010, F, NE, U, ZE	●		●	
	915	FUORI Aluminium and Delrin handle, for external and internal openings, dist. between centres 104-108 mm, 2 cap screws Ø 3,9x25 in galvanized steel and 2 cap screws M4x18 in black galvanized steel.	20	1013, 6005, 8017, 9001, 9010, F, NE, U, ZE	●		●	
	916.897	Kit for art. 915/.1 including 2 cap screws M4x18 and 4 plates in galvanized steel.	40				●	
	996.24	RENZO Fixing device in galvanized steel, nylon adjustment screw.	100			●		
	1115	MORSADUE+ (patented) Two-wing hinge in aluminium, 2 nylon bushings, galvanized steel pin, pre-assembled counterplates and 4 countersunk oval head screws M5x10 in stainless steel 430. Weight capacity: 2 hinges Kg 60, 3 hinges Kg 70.	50	1013, 1015, 1247, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B,SA, BL10, BR801, C, F, GR217, GR50, GR51, GR606, HL, NE, RD501, SILV, U, WT005, ZE	●		●	
	1118	PLUS Two-wing aluminium hinge, nylon bushings and caps, pin, counterplates and 5 countersunk head screws M5x8 in stainless steel 430. Weight capacity: 2 hinges 60 Kg, 3 hinges 70 Kg.	50	1013, 1015, 3003, 6005, 8017, 8019, 9001, 9005, 9010, C, F, NE, U, ZE	●		●	
	1120	TRIAL Three-wing pre-assembled aluminium hinge, nylon bushings and caps, pin, counterplates and 7 countersunk head screws M5x8 in stainless steel 430. Weight capacity: 2 hinges 80 Kg, 3 hinges 90 Kg.	20	1013, 3003, 6005, 8017, 9001, 9010, C, F, HL, NE, U, ZE	●		●	









	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1121	MORSA+ (patented) Two-wing aluminium hinge, nylon bushing, pin, counterplates and 4 pre-assembled countersunk oval head screws M5x10 in stainless steel 430. Weight capacity: 2 hinges 80 Kg, 3 hinges 90 Kg (PVD H, PVD X, XSD=pack. 20 pcs.).	50	1013, 1015, 1247, 3003, 6002, 6005, 7035, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, F, GR217, GR50, GR51, GR606, HL, NE, PVD H, PVD X, RD501, SILV, U, WT005, XSD, ZE	●		●	
	1121D	MORSA+ Like 1121 but pre-assembled right hand.	50	1013, 1015, 9005, 9010, B.SA, BL10, F, NE, ZE	●		●	
	1121S	MORSA+ Like 1121 but pre-assembled left hand.	50	1013, 1015, 9005, 9010, B.SA, BL10, F, NE, SILV, ZE	●		●	
	1122	MORSA+ (patented) Three-wing preassembled aluminium hinge, nylon bushings, pins, counterplates and 6 pre-assembled countersunk oval head screws M5x10 in stainless steel 430. Weight capacity: 2 hinges 90 Kg, 3 hinges 100 Kg (XSD: pack. 10 pcs.).	20	1013, 1015, 3003, 6002, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR801, BW21, C, F, GR217, GR606, HL, NE, RD501, SILV, U, WT005, XSD, ZE	●		●	
	1122.200	MORSA+ (patented) 3-wing pre-assembled hinge in aluminium, nylon bushing, pre-assembled extractable pin, indented plates and 6 pre-assembled countersunk head screws M5x9 in stainless steel 430. Carryng capacity: 2 hinges 90 Kg., 3 hinges Kg. 100 (PVD H, PVD X, XSD: pack. 10 pcs.).	20	1013, 1015, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, F, GR217, GR606, HL, NE, PVD H, PVD X, RD501, SILV, U, WT005, XSD, ZE	●		●	
	1124.30	SUMMA (patented) 2 wing adjustable hinge in aluminium, centre of rotation 16 mm, 2 quick clamping counterplates, 4 socket head cap screws M6x12 and 1 grub screw M5x6 in stainless steel, 1 stainless steel 10 mm pin pre-assembled on black galvanized zamak cam bushing device, 2 nylon caps, 1 self-lubricating bushing in nylon, 1 adjustment grub screw in zamak. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg (HL, PVD H, PVD X, XSD: pack. 4 pcs.).	20	1013, 1015, 1247, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BL25, BR5, BR801, BW21, C, F, GR217, GR50, GR51, GR606, HL, NE, PVD H, PVD X, SILV, WT005, XSD, ZE	●		●	
	1125	SCUDO Two-wing hinge (dist.between centres 60 mm), centre of rotation 20 mm, in aluminium, step 0 mm, pin in stainless steel 430, bushing and washer in nylon, 2 aluminium counterplates, 2 grub screws M5x10 and 4 countersunk head screws M8x30 in galvanized steel. Weight capacity: 2 hinges 120 Kg, 3 hinges 140 Kg.	4	1013, 1015, 3003, 6005, 8017, 9001, 9005, 9010, 9016, B.SA, C, F, GR217, GR606, HL, NE, U, ZE		●		●
	1125.2	SCUDO Two-wing hinge (dist.between centres 78 mm), centre of rotation 20 mm, in aluminium, step 0 mm, pin in stainless steel 430, bushing and washer in nylon, 2 aluminium counterplates, 2 grub screws M5x10 and 4 countersunk head screws M8x30 in galvanized steel. Weight capacity: 2 hinges 120 Kg, 3 hinges 140 Kg.	4	1013, 3003, 6005, 9001, 9010, B.SA, C, F, NE, U, ZE		●		
	1130.1/60	TEKNICA (patented) 2-wing adjustable door hinge, distance between centres 60 mm, centre of rotation 36 mm, step 0 mm, in aluminium, pin Ø 15 in stainless steel 430, 2 pre-assembled grub screws in galvanized brass for pin adjustment, 1 bushing in Delrin, 1 washer in black powder coated zamak, 2 counterplates in zamak, 2 springs for counterplates in black galvanized steel (C70), 2 nylon caps, 1 stop release safety pin in steel, 4 socket head cap screws M8x31, 2 screws for coverplates fixing in galvanized steel. Weight capacity: 2 hinges Kg 120, 3 hinges Kg 140.	8	1013, 1015, 9005, 9010, B.SA, C, F, GREY, HL, NE, ZE		●		●

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1130.1/79	TEKNICA Like 1130.1/60 but with dist.between centres of 79 mm.	8	1013, 9005, 9010, C, F, NE, ZE		●		●
	1130.1/93	TEKNICA Like 1130.1/60 but with dist.between centres of 93 mm.	8	1013, 9005, 9010, C, F, NE, ZE		●		●
	1131.1/60	TEKNICA (patented) 3-wing adjustable door hinge, distance between centres 60 mm, centre of rotation 36 mm, step 0 mm, in aluminium, pin Ø 15 in stainless steel 430, 2 pre-assembled grub screws in galvanized brass for pin adjustment, 2 bushings and 2 washers in Delrin, 1 black powder coated zamak washer, 3 counterplates in zamak, 3 springs for counterplates in black galvanized steel (C70), 1 nylon spacer for counterplates, 2 nylon caps, 1 stop release safety pin in steel, 6 socket head cap screws M8x31, 3 screws for coverplates fixing in galvanized steel. Weight capacity: 2 hinges Kg 120, 3 hinges Kg 140.	8	1013, 9005, 9010, 9016, C, F, NE, ZE		●		●
	1131.1/79	TEKNICA Like 1131.1/60 but with dist.between centres of 79 mm.	8	1013, 9005, 9010, C, F, NE, ZE		●		●
	1131.1/93	TEKNICA Like 1131.1/60 but with dist.between centres of 93 mm.	8	1013, 9005, 9010, C, F, NE, ZE		●		●
	1139	TEKNICA Aluminium hinge pivot, center of rotation 36 mm, 1 counterplate in zamak, 1 spring for counterplate in black galvanized steel (C 70), 1 nylon cap, 2 socket head cap screws M8x31, 4 self-tapping socket head cap screws Ø 6,3x22, 4 crinkled washers and 1 screw for coverplate fixing in galvanized steel (for the art. 1130.1/60; 1130.1/79;1131.1/60;1131.1/79).	2	1013, 9005, 9010, 9016, B.SA, C, F, NE, ZE		●		●
	1145/53	MECHANICA (patented) 2-wing adjustable door hinge for narrow frame, distance between centres of 53 mm, centre of rotation 20 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on a black galvanized zamak cam bushing, 2 aluminium coverplates, 2 nylon caps, 1 self-lubricating bushing, 1 zamak adjustment grub screw. Complete with galvanized fastening kit, including: 1 zamak counterplate 14x14 mm, 1 pre-hardened burnished steel leaf spring, 1 extruded aluminium counterplate 9x14 mm, 2 galvanized special screws M6x20 for counterplate fixing (leaf side), 2 galvanized screws M8x28 for counterplate fastening (frame side), 2 centering bushings for frame wing, 1 galvanized socket head cap screw M4x16 and 1 galvanized socket head cap screw M4x14 for coverplate fixing, 1 galvanized grub screw M6x8 for cam bushing fastening. Weight capacity: 2 hinges 80 Kg, 3 hinges 100 Kg (HL, PVD H, PVD X, XSD=pack. 4 pcs.)	20	1013, 1247, 6005, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, F, GR217, GR50, GR51, GR606, HL, NE, PVD H, PVD X, SILV, WT005, XSD, ZE		●		●
	1145/60MR	MECHANICA Like 1145/53 but distance between centres of 60 mm. Weight capacity: 2 hinges 60 Kg, 3 hinges 80 Kg.	20	1013, 9001, 9010, F, NE, PVD H, XSD		●		●
	1145/67MR	MECHANICA Like 1145/60MR but distance between centres of 67 mm.	20	9005, 9010, C, F, GR217, NE, SILV		●		●
	1145/60	MECHANICA (patented) 2-wing adjustable door hinge made of aluminium, distance between centres of 60 mm, centre of rotation 20 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on black galvanized zamak cam bushing device, 2 aluminium coverplates, 2 nylon caps, 1 nylon self-lubricating bushing, 1 zamak adjustment grub screw. Weight capacity: 2 hinges 160 Kg, 3 hinges 180 Kg (HL, PVD H, PVD X, XSD=pack. 4 pcs.).	20	1013, 1015, 1247, 6005, 7032, 7035, 7047, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, F, GR217, GR50, GR51, GR606, HL, NE, PVD H, PVD X, SILV, WT005, XSD, ZE		●		●
	1145/67	MECHANICA Like 1145/60 but distance between centres of 67 mm.	20	1013, 1015, 1247, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, F, GR217, GR606, HL, NE, PVD H, PVD X, RD501, SILV, WT005, XSD, ZE		●		●

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1145/79	MECHANICA Like 1145/60 but distance between centres of 79 mm. Weight capacity: 2 hinges 120 Kg, 3 hinges 140 Kg.	20	1013, 1247, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, C, F, GR217, GR50, GR51, GR606, HL, NE, PVD X, SILV, WT005, XSD, ZE		●		●
	1145/86	MECHANICA Like 1145/60 but distance between centres of 86 mm. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg.	20	1013, 9005, 9010, BL10, C, F, NE, PVD X, SILV, XSD		●		●
	1145/93	MECHANICA Like 1145/86 but distance between centres of 93 mm.	20	1013, 1247, 6005, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, C, F, GR217, GR606, HL, NE, PVD H, PVD X, RD501, SILV, XSD, ZE		●		●
	1145/93SM	MECHANICA Like 1145/93 but with 2 symmetric wings.	20	1013, 1247, 9005, 9010, 9016, B.SA, BR5, C, F, NE, SILV, XSD, ZE		●		
	1145.3/53	MECHANICA (patented) 3-wing adjustable door hinge for narrow frame, distance between centres of 53 mm, centre of rotation 20 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on a black galvanized zamak cam bushing, 2 aluminium coverplates, 2 nylon caps, 1 self-lubricating bushing, 1 zamak adjustment grub screw. Complete with galvanized fastening kit, including: 1 zamak counterplate 14x14 mm, 1 pre-hardened burnished steel leaf spring, 1 extruded aluminium counterplate 9x14 mm, 2 galvanized special screws M6x20 for counterplate fixing (leaf side), 2 galvanized screws M8x28 for counterplate fastening (frame side), 2 centering bushings for frame wing, 1 galvanized socket head cap screw M4x16 and 1 galvanized socket head cap screw M4x14 for coverplate fixing, 1 galvanized grub screw M6x8 for cam bushing fastening. Weight capacity: 2 hinges 80 Kg, 3 hinges 100 Kg.	10	6005, 9005, 9010, C, F, NE, ZE		●		●
	1145.3/60	MECHANICA (patented) 3-wing adjustable door hinge made of aluminium, distance between centres of 60 mm, centre of rotation 20 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on black galvanized zamak cam bushing device, 3 aluminium coverplates, 2 nylon caps, 2 nylon self-lubricating bushings, 1 zamak adjustment grub screw, 1 nylon spacer for counterplates and 1 rubber ring. Weight capacity: 2 hinges 160 Kg, 3 hinges 180 Kg (HL, PVD H, PVD X, XSD=pack. 4 pcs.).	10	1013, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BW21, C, F, GR217, GR50, HL, NE, PVD X, SILV, WT005, XSD, ZE		●		●
	1145.3/67	MECHANICA Like 1145.3/60 but distance between centres of 67 mm.	10	1013, 6005, 8019, 9001, 9005, 9010, 9016, BL10, BR5, C, F, GR217, GR606, HL, NE, PVD H, PVD X, SILV, XSD, ZE		●		●
	1145.3/79	MECHANICA Like 1145.3/60 but distance between centres of 79 mm. Weight capacity: 2 hinges 120 Kg, 3 hinges 140 Kg.	10	1013, 8019, 9005, 9010, 9016, BL10, C, F, GR217, HL, NE, PVD X, SILV, WT005, XSD, ZE		●		●
	1145.3/86	MECHANICA Like 1145/60 but distance between centres of 86 mm. Weight capacity: 2 hinges 160 Kg, 3 hinges 180 Kg.	10	F, NE		●		●
	1145.3/93	MECHANICA Like 1145.3/86 but distance between centres of 93 mm. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg.	10	1013, 8019, 9005, 9010, 9016, BL10, BR5, C, F, GR217, GR50, HL, NE, PVD X, SILV, XSD, ZE		●		●
	1145.3/93SM	MECHANICA Like 1145.3/93 but with 3 symmetric wings.	1	1013, 9010, C, F, GR217, NE, PVD H, PVD X, SILV, WT005		●		

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1145.704	(patented) Galvanized fastening kit for 2-wing MECHANICA hinges on flat profiles, with: 2 zamak counterplates 14x14 mm, 4 galvanized special screws for counterplate fastening M8x28, 2 galvanized socket head cap screws M4x16 for cover fastening, 1 galvanized grub screw M6x8 for cam bushing fastening, 2 pre-hardened burnished steel leaf springs.	20			●		●
	1145.705	(patented) Stainless steel fastening kit for 2-wing MECHANICA hinges on flat profiles, with: 2 zamak counterplates 14x14 mm, 4 stainless steel special screws for counterplate fastening M8x28, 2 stainless steel socket head cap screws M4x16 for cover fastening, 1 stainless steel grub screw M6x8 for cam bushing fastening, 2 stainless steel leaf springs.	20			●		●
	1145.706	(patented) Galvanized fastening kit for 2-wing MECHANICA hinges on flat profiles, with: 2 zamak counterplates 20x11 mm, 4 galvanized special screws for counterplate fastening M8x28, 2 galvanized socket head cap screws M4x16 for cover fastening, 1 galvanized grub screw M6x8 for cam bushing fastening, 2 pre-hardened burnished steel leaf springs.	20			●		●
	1145.707	(patented) Stainless steel fastening kit for 2-wing MECHANICA hinges on flat profiles, with: 2 zamak counterplates 20x11 mm, 4 stainless steel special screws for counterplate fastening M8x28, 2 stainless steel socket head cap screws M4x16 for cover fastening, 1 stainless steel grub screw M6x8 for cam bushing fastening, 2 stainless steel leaf springs.	20			●		●
	1145.714	(patented) Galvanized fastening kit for 3-wing MECHANICA hinges on flat profiles, with: 3 zamak counterplates 14x14 mm, 6 galvanized special screws for counterplate fastening M8x28, 3 galvanized socket head cap screws M4x16 for cover fastening, 1 galvanized grub screw M6x8 for cam bushing fastening, 3 pre-hardened burnished steel leaf springs.	10			●		●
	1145.715	(patented) Stainless steel fastening kit for 3-wing MECHANICA hinges on flat profiles, with: 3 zamak counterplates 14x14 mm, 6 stainless steel special screws for counterplate fastening M8x28, 3 stainless steel socket head cap screws M4x16 for cover fastening, 1 stainless steel grub screw M6x8 for cam bushing fastening, 3 stainless steel leaf springs.	10			●		●
	1145.805	(patented) Zamak width adapter for counterplate 14x14 mm.	100			●		●
	1146/59	MECHANICA (patented) 2-wing adjustable door hinge made of aluminium, distance between centres of 59 mm, centre of rotation 20 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on black galvanized zamak cam bushing device, 2 aluminium coverplates, 2 nylon caps, 1 nylon self-lubricating bushing, 1 zamak adjustment grub screw. Weight capacity: 2 hinges 160 Kg, 3 hinges 180 Kg.	20	9016, F, ZE		●		●
	1146/62.5	MECHANICA Like 1146/59 but distance between centres of 62.5 mm.	20	1013, 1015, 1247, 7016, 7047, 8017, 8077, 9001, 9005, 9010, 9016, B.SA, C, F, HL, NE, SILV, XSD, ZE		●		●








	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1146/67	MECHANICA Like 1146/59 but distance between centres of 67 mm.	20	1015, 1247, 8019, 9005, 9010, 9016, B.SA, C, F, NE, SILV, ZE		●		●
	1146/74.5	MECHANICA Like 1146/59 but distance between centres of 74.5 mm. Weight capacity: 2 hinges 120 Kg, 3 hinges 140 Kg.	20	9016, C, F, ZE		●		●
	1146/78	MECHANICA Like 1146/59 but distance between centres of 78 mm. Weight capacity: 2 hinges 120 Kg, 3 hinges 140 Kg.	20	1013, 1247, 8019, 8077, 9005, 9010, 9016, B.SA, C, F, NE, PVD X, XSD, ZE		●		●
	1146/84	MECHANICA Like 1146/59 but distance between centres of 84 mm. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg.	20	1013, 1247, 8077, 9005, 9010, 9016, B.SA, BL10, C, F, NE, PVD X, SILV, ZE		●		●
	1146/89	MECHANICA Like 1146/84 but distance between centres of 89 mm.	20	9005, 9010, 9016, C, F, NE, ZE		●		
	1146/92	MECHANICA Like 1146/59 but distance between centres of 92 mm. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg.	20	1013, 1247, 8019, 8077, 9005, 9010, 9016, B.SA, C, F, NE, ZE		●		●
	1146/97	MECHANICA Like 1146/92 but distance between centres of 97 mm.	20	1247, 9005, 9010, 9016, B.SA, C, F, NE, SILV, ZE		●		
	1146/104	MECHANICA Like 1146/92 but distance between centres of 104.5 mm (PVD X, XSD=pack. 4 pcs.)	20	1013, 9005, 9010, 9016, C, F, NE, PVD X, XSD, ZE		●		
	1146.1/62.5	MECHANICA (patented) 2-wing adjustable door hinge made of aluminium, distance between centres of 62.5 mm, centre of rotation 36 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on black galvanized zamak cam bushing device, 2 aluminium coverplates, 2 nylon caps, 1 nylon self-lubricating bushing and 1 zamak adjustment grub screw. Weight capacity: 2 hinges 160 Kg, 3 hinges 180 Kg (HL, PVD H, PVD X, XSD=pack. 4 pcs.).	20	1013, 9005, 9010, 9016, B.SA, C, F, NE, PVD X, XSD, ZE		●		●
	1146.1/84	MECHANICA Like 1146.1/62.5 but distance between centres of 84 mm. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg.	20	1013, 9005, 9010, C, F, NE, ZE		●		●
	1146.3/59	MECHANICA (patented) 3-wing adjustable door hinge made of aluminium, distance between centres of 59 mm, centre of rotation 20 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on black galvanized zamak cam bushing device, 3 aluminium coverplates, 2 nylon caps, 2 nylon self-lubricating bushings, 1 zamak adjustment grub screw, 1 nylon spacer for counterplates and 1 rubber ring. Weight capacity: 2 hinges 160 Kg, 3 hinges 180 Kg.	10	9010, 9016, F, ZE		●		●
	1146.3/62.5	MECHANICA Like 1146.3/59 but distance between centres of 62.5 mm.	10	1013, 8017, 9005, 9010, 9016, B.SA, C, F, NE, PVD X, SILV, XSD, ZE		●		●
	1146.3/67	MECHANICA Like 1146.3/59 but distance between centres of 67 mm.	10	9010, 9016, F, ZE		●		●
	1146.3/74.5	MECHANICA Like 1146.3/59 but distance between centres of 74.5 mm. Weight capacity: 2 hinges 120 Kg, 3 hinges 140 Kg.	10	9016, F, ZE		●		●
	1146.3/78	MECHANICA Like 1146.3/74.5 but distance between centres of 78 mm.	10	1013, 8077, 9005, 9010, 9016, C, F, NE, ZE		●		●
	1146.3/84	MECHANICA Like 1146.3/59 but distance between centres of 84 mm. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg.	10	1013, 8077, 9005, 9010, 9016, C, F, NE, PVD X, ZE		●		●



PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1146.3/89	MECHANICA Like 1146.3/84 but distance between centres of 89 mm.	10	9005, 9010, 9016, C, F, SILV, XSD, ZE		●		
	1146.3/92	MECHANICA Like 1146.3/84 but distance between centres of 92 mm.	10	1013, 9001, 9005, 9010, 9016, C, F, NE, ZE		●		●
	1146.3/97	MECHANICA Like 1146.3/92 but distance between centres of 97 mm.	10	9005, 9016, F, ZE		●		
	1146.3/104	MECHANICA Like 1146.3/97 but distance between centres of 104.5 mm.	10	9016, F, NE, ZE		●		
	1146.13/62.5	MECHANICA (patented) 3-wing adjustable door hinge made of aluminium, distance between centres of 62.5 mm, centre of rotation 36 mm, step 0 mm, 1 stainless steel pin Ø 11 mm, pre-assembled on black galvanized zamak cam bushing device, 3 aluminium coverplates, 2 nylon caps, 2 nylon self-lubricating bushings, 1 zamak adjustment grub screw, 1 nylon spacer for counterplates and 1 rubber ring. Weight capacity: 2 hinges 160 Kg, 3 hinges 180 Kg.	10	1013, 9005, 9010, C, F, NE, SILV, ZE		●		●
	1146.13/84	MECHANICA Like 1146.13/62.5 but distance between centres of 84 mm. Weight capacity: 2 hinges 100 Kg, 3 hinges 120 Kg.	10	1013, 9005, 9010, C, F, NE, ZE		●		●
	1147	MECHANICA (patented) Aluminium hinge pivot, centre of rotation 36 mm, 1 zamak counterplate 14x14 mm, 1 stainless steel spring leaf, 2 stainless steel special screws M8x28 for counterplate fastening, 4 galvanized self-tapping socket head cap screws Ø 6.3x22, 4 galvanized crinkled washers, 1 stainless steel socket head cap screw M5x25 for counterplate fastening, 1 nylon cap.	2	1013, 9005, 9010, C, F, NE, PVD X, SILV, XSD, ZE		●		●
	1160	VOLVO Kit of concealed hinges in stainless steel and black galvanized zamak, pre-assembled top end, screws and grub screws in stainless steel. Weight capacity: max Kg 80.	10		●		●	
	1160.801	Adjustable supplementary locking point in black galvanized zamak, pre-assembled screws and grub screws in stainless steel.	40		●		●	
	1170.4	KLEM Hinge and 4 countersunk head screws Ø 4.8x13 in galvanized steel. Weight capacity: 2 hinges 15 Kg for bottom hung casement; 30 Kg for top hung casement opening out.	20		●		●	
	1180.5	KLEMDUE Double-opening hinge, 1 nylon cup, 2 cap screws Ø 4.8x13, 1 countersunk head screw Ø 4.8x13, 1 cap screws M5x6 in galvanized steel and 1 supporting plate. Weight capacity: 2 hinges 15 Kg for bottom hung casement.	20		●		●	
	1200/7	MONO Mono directional gearbox with 8 mm backset for RIBANTATRE and RIBANTA 4, in black galvanized zamak, 7 mm square hole, nylon bushings Ø 6-Ø 8 mm.	5		●		●	









	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1200/8	MONO Like 1200/7 but with 8 mm backset.	5		●		●	
	1201/7	DUO Bi-directional movement mechanism for case-ment opening, with 8 mm backset, in black galvanized zamak, 7 mm square hole, nylon bushings Ø 6-Ø 8 mm.	20		●		●	
	1201/8	DUO Like 1201/7 but with 8 mm backset.	20		●		●	
	1202/7	Bi-directional movement with 22 mm backset made of black galvanized zamak, 7 mm square hole, 2 nylon bushings Ø 6-Ø 8 mm.	20		●			
	1206/1	SINTESI (patented) Folding opener in aluminium, nylon and stainless steel 430, 1 preassembled cap screw M4x6 and 4 countersunk head screws M5x12 in stainless steel 304 (self forming thread).	10	1013, 1015, 9010, F, NE, ZE	●			
	1206/2	SINTESI Like 1206/1 but measure /2.	10	1015, 9001, 9010, 9016, F, NE, SILV, U, ZE	●			
	1206.1/1	SINTESI (patented) Releasable folding opener in aluminium, nylon and stainless steel 430, 1 preassembled cap screw M4x5 and 4 countersunk head screws M5x12 in stainless steel 304 (self forming thread).	10	9010, F, NE, ZE	●			
	1206.1/2	SINTESI Like 1206.1/1 but measure /2.	10	9010, F, NE, ZE	●			
	1210/7	MONO Mono directional gearbox for tilt and turn windows with 14,5 mm backset, in black galvanized zamak, 7 mm square hole, nylon bushings Ø 6-Ø 8 mm.	5		●		●	
	1211/7	DUO Bi-directional movement mechanism for case-ment opening, with 14,5 mm backset, in black galvanized zamak, 7 mm square hole, nylon bushings Ø 6-Ø 8 mm.	20		●		●	
	1243.599	Aluminium loose grip handle for art. 870.755/.756-872 .752-873.755/.756.	1	1013, 7035, 9010, C, F, NE, SILV	●		●	
	1243.704	Handle connection piece in black galvanized zamak, 2 polyurethane caps.	10		●		●	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1243.710	Locking piece in black galvanized zamak, 1 polyurethane cap.	5		●		●	
	1243.721	Adjustable keeper in black galvanized zamak, 2 pre-assembled grub screws M5x12 and 1 countersunk head screw M4x8 in stainless steel 304.	40		●		●	
	1243.721W	Like 1243.721 but in white galvanized zamak.	40		●		●	
	1243.750	Aluminium handle for RIBANTATRE, distance between centres 84.5-92-98-104 mm, 2 socket head cap screws M5x10 in stainless steel 304.	5	1013, 3003, 6005, 8017, 9001, 9005, 9010, BW21, C, F, NE, SILV, U, ZE	●		●	
	1243.790	Upper corner drive in black galvanized zamak.	10		●		●	
	1246.832	Hinge-side supplementary closing point in black galvanized zamak, 3 pre-assembled grub screws M5x12 and 1 countersunk head screw M4x8 in stainless steel 304.	40		●		●	
	1246.832W	Like 1246.832 but in white galvanized zamak.	40		●		●	
	1246.835	Non-handed anti-burglar device for grooves 13,5x16,5 and 14x18, in black galvanized zamak, 2 countersunk head screws M5x18 in stainless steel 304 (self-forming), 2 nylon bushings Ø 6-Ø 8 mm.	40		●		●	
	1307.1	MARCO INOX Adjustable multiposition arm for top hung casement opening out, in stainless steel 430, 2 hinge pivots (9 mm) and 2 nylon spacer (4 mm), 4 countersunk head screws Ø 4.8x25 in stainless steel 304. Suitable for profiles with clearance of 21-30 mm. Weight capacity: 2 arms 70 Kg.	20		●			
	1341	PIOVRATRE (patented) Releasable arm stay in stainless steel 304, zamak counterplates, 4 preassembled grub screws M5x6 in galvanized steel. For Euro groove/ NC International profiles and for grooves 10x14,3-12x15-14x18-12,5x16,5-13,5x16,5. Weight capacity: 2 arms 70 Kg.	20		●		●	
	1343.2	Damping-effect opening restrictor arm in zamak, nylon, polyurethane and stainless steel 304, 2 grub screws M5x8 in galvanized steel and 2 M5x12 in stainless steel 304.	10		●		●	
	1343.4	Damping-effect opening limiter arm stay in black galvanized zamak, polyurethane and stainless steel 304, 2 grub screws M5x8 and 2 pre-assembled grub screws M5x12 in stainless steel 304.	10		●		●	


	Code	DESCRIPTION	POS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1343.8L/20	LH frictioning opening limiter arm stay, 20 cm, in zamak, nylon and stainless steel 304, 3 preassembled grub screws M5x12 in stainless steel 304.	20		●		●	
	1343.8L/60	Like 1343.8L/20 but of 60 cm.	20		●		●	
	1343.8R/20	Like 1343.8L/20 but right hand.	20		●		●	
	1343.8R/60	Like 1343.8R/20 but of 60 cm.	20		●		●	
	1344	PIOVRADUE (patented) Releasable arm stay in stainless steel 304, counterplates in black galvanized zamak, 2 grub screws M5x6 and 2 grub screws M5x10, pre-assembled, in stainless steel. Weight capacity: 2 arms 70 Kg.	20		●		●	
	1344.4	PIOVRADUE Like 1344.	20		●		●	
	1345	Horizontal releasable arm stay for bottom hung casement in stainless steel 304, galvanized zamak base, 2 stainless steel 303 grub screws, 1 grub screw M5x6 and 2 grub screws M5x10 in stainless steel, 1 nylon sliding guide, 1 nylon stopping block. Fit for profiles with clearance mm 21÷31,5. Application field: Upper side horizontal assembly. Casement minimum height: 400 mm - Maximum width: until 1200 mm with 1 arm, up to 1200 mm with 2 arms. Bottom hung casement maximum opening: 200 mm. Groove of the leaf: 20 or 23 mm. Weight capacity: 1 arm 50 Kg., 2 arms 70 Kg.	20		●		●	
	1390.1	REGOLO (patented) Preassembled clamp-in catch in black galvanized zamak, 2 self-tapping fitting screws in galvanized steel, adjustable keeper, 1 steel spring.	50	.74, .75, .78	●		●	
	1404	Keeper in black galvanized zamak, wing nut and 1 pre-assembled countersunk head screw M5x10 in stainless steel 304.	100		●		●	
	1410.701	Support in zamak, 1 pre-assembled grub screw M5x6 in galvanized steel.	100		●		●	
	1410.705	Black nylon support.	100		●		●	
	1411.1	Keeper for art. 1556 in black galvanized zamak, 2 cap screws Ø 3,9x13 in galvanized steel.	50					●







PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1414	Adjustable keeper in black galvanized zamak, 1 pre-assembled grub screw M5x12 in stainless steel, 2 nylon cups.	200		●		●	
	1414W	Like 1414 but in white galvanized zamak.	200		●		●	
	1414.1W	Double adjustable keeper in white galvanized zamak, 2 pre-assembled grub screws M5x12 in stainless steel, 3 black nylon spacers (0.6 - 1 - 1.5 mm).	200		●		●	
	1415	Double keeper in black galvanized zamak, 2 pre-assembled grub screws M5x10 in galvanized steel.	100		●		●	
	1416.5	Double keeper in black galvanized zamak, 1 pre-assembled grub screw M5x10 in galvanized steel.	100		●		●	
	1416.5W	Like 1416.5 but in white galvanized zamak.	100		●		●	
	1463	Ventilation locking piece available for 3rd locking point too, in black nylon (to combine with art. 1416.5).	100		●		●	
	1464	Intermediate locking piece in black galvanized zamak.	100		●		●	
	1465	Terminal locking piece in black galvanized zamak, 1 polyurethane cap and 1 nylon bushing Ø 6-Ø 8.	100		●		●	
	1481	Connection piece in black galvanized zamak, 1 polyurethane cap, 1 nylon bushing Ø 6-Ø 8.	200		●		●	



	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1481.8	Connection piece in white galvanized zamak, 1 clip and 1 nylon bushing Ø 6-Ø 8.	200		•		•	
	1484.4	Nylon connection piece.	200		•		•	
	1484.7	Couple of connection pieces with ventilation switch and 1 bushing Ø 6-Ø 8 in black nylon.	100		•		•	
	1484.8	Couple of connection pieces and 1 bushing Ø 6-Ø 8 in black nylon.	100		•		•	
	1485	Black nylon terminal rod closing piece, top end in galvanized steel Ø 8 with adjustable nylon bushing.	100		•		•	
	1485.8	Black nylon terminal rod closing piece, top end in galvanized steel Ø 8 with adjustable nylon bushing, 1 nylon bushing Ø 6-Ø 8.	100		•		•	
	1486	Terminal rod closing piece in black galvanized zamak, 2 polyurethane caps and 1 nylon bushing Ø 6-Ø 8.	100		•		•	
	1486.8	Terminal rod closing piece in white galvanized zamak, 1 clip and 1 nylon bushing Ø 6-Ø 8, 1 polyurethane cap in red nylon.	100		•		•	
	1487.1	Adjustable terminal rod closing piece in black galvanized zamak and stainless steel 430, 1 polyurethane cap and 1 nylon bushing Ø 6-Ø 8.	100		•		•	









PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1487.8	Adjustable terminal rod closing piece in white galvanized zamak, pre-assembled black nylon clips.	100		●		●	
	1557/13	IPER REVERTO (patented) Lever bolt 13 cm (travel 22 mm) in zamak, pin and 3 countersunk head screws Ø 3.9x19 in stainless steel.	20	9005, 9010, B.SA, BR5, GR217, SILV				●
	1557/20	IPER REVERTO Like 1557/13 but 20 cm.	20	1013, 6005, 9005, 9010, B.SA, BL10, GR217, GR50, GR51, SILV				●
	1557/45	IPER REVERTO Like 1557/13 but 45 cm.	20	9005, 9010, B.SA, BL10, BR5, GR217, SILV				●
	1557/65	IPER REVERTO Like 1557/13 but 65 cm.	10	9005, 9010, B.SA, GR217, SILV				●
	1570.801	Kit of 1 spacer 7.3 mm, 1 spacer 3 mm, 1 spacer 1.2 mm and 2 countersunk head screws Ø 4.2x25 in stainless steel.	50			●		●
	1572.801	Kit composed of: keeper (outer body in painted ABS liquid varnished, core in Zamak), 1 spacer of 5 mm, 2 spacers of 4 mm, 1 spacer of 2 mm made of nylon, 3 cap screws Ø 4.2x32 in white galvanized steel.	10	.74, .78, 1013, 8019, SILV		●		●
	1604	SELLA Handle in brass, distance between centres of 43 mm, 7 mm square spindle and 2 countersunk head screws M5x35 in galvanized steel (to combine with art. 1200/7 and 1201/7).	5	OTT	●		●	
	1604.899	Kit of a 7 mm square spindle and 2 countersunk head screws M5x50 in galvanized steel (to combine with art. 1604 and 1605, for wood-aluminium mixed profiles).	50		●			
	1605	STAFFA Handle in brass, distance between centres of 43 mm, 7 mm square spindle and 2 countersunk head screws M5x35 in galvanized steel (to combine with art. 1200/7 and 1201/7).	5	OTT	●		●	
	1606	GINEVRA Stainless steel (AISI 304) handle, distance between centres 43 mm, square spindle 7 mm, 2 stainless steel countersunk head screws M5x45. It can be combined with movement mechanisms MONO (art. 1200/7) and DUO (art. 1201/7).	2	PVD H, S	●		●	
	1607	GINEVRA Stainless steel (AISI 304) handle, distance between centres 43 mm, square spindle 7 mm, 2 stainless steel countersunk head screws M5x45. It can be combined with movement mechanisms MONO (art. 1200/7) and DUO (art. 1201/7).	2	PVD H, S	●		●	

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1608	GINEVRA Stainless steel (AISI 304) handle, distance between centres 43 mm, square spindle 7 mm, 2 stainless steel countersunk head screws M5x45. It can be combined with movement mechanisms MONO (art. 1200/7) and DUO (art. 1201/7).	2	PVD H, S	●		●	
	1609	Snap-latch with reduced base and handle made of aluminum and nylon with 7 mm squared spindle and 2 zinc-plated steel countersunk head screw M5x35.	5	9005, 9010, C, SILV	●		●	
	1609.1	Snap-latch with reduced base and handle made of aluminum and nylon with square spindle (62,5mm projecting part) and 2 zinc-plated steel countersunk head screw M5x70.	5	9005, 9010, C, SILV	●			
	1625	RUMBA Aluminium double door handle, 2 pre-assembled grub screws M6x10 in galvanized steel and 4 countersunk head screws Ø3,5x13 in stainless steel 304.	10	1013, 3003, 6005, 8017, 9010, F, GR50, GR51, NE, U, ZE				●
	1636	CHARLESTON Aluminium double door handle, 2 pre-assembled grub screws M6x8 in galvanized steel and 4 countersunk head screws Ø 3,5x13 in stainless steel 304.	10	1013, 1015, 3003, 6005, 9010, 9016, B,SA, C, F, NE, U, ZE				●
	1640	SELLA Double door handle in solid brass, with spring return, 4 countersunk head screws Ø 3,5x16 in galvanized steel.	4	OTT				●
	1641	STAFFA Double door handle in solid brass, with spring return, 4 countersunk head screws Ø 3,5x16 in galvanized steel.	4	OTT				●
	1642	GINEVRA Stainless steel (AISI 304) double door handle with return spring and square spindle 8x120 mm, 2 escutcheons for shaped cylinder, 8 stainless steel countersunk head screws Ø 4,2x19.	2	PVD H, S		●		●
	1642.1	GINEVRA Like 1642 but with 2 escutcheons for oval cylinder.	2	PVD H, S		●		●

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1643	GINEVRA Stainless steel (AISI 304) double door handle with return spring and square spindle 8x120 mm, 2 escutcheons for shaped cylinder, 8 stainless steel countersunk head screws Ø 4,2x19.	2	PVD H, S		•		•
	1643.1	GINEVRA Like 1643 but with 2 escutcheons for oval cylinder.	2	PVD H, S		•		•
	1644	GINEVRA Stainless steel (AISI 304) double door handle with return spring and square spindle 8x120 mm, 2 escutcheons for shaped cylinder, 8 stainless steel countersunk head screws Ø 4,2x19.	2	PVD H, S		•		•
	1644.1	GINEVRA Like 1644 but with 2 escutcheons for oval cylinder.	2	PVD H, S		•		•
	1665.801	Single handle attachment for art. 1666, in galvanized steel and nylon.	20					•
	1666	AZALEA Double door handle in aluminium and nylon, 2 pre-assembled grub screws M6x8 and 6 countersunk head screws Ø3,5x13 in galvanized steel.	10	1013, 3003, 6005, 9010, C, F, NE, U, ZE				•
	1801.1	EXCALIBUR Nylon 6 handle with pre-mounted stainless steel set screws. Diameter 35 mm.	2	.74, .78, .79, .81		•		•
	1801.2	EXCALIBUR Nylon 6 handle with pre-mounted stainless steel set screws. Diameter 35 mm.	2	.74, .79, .81		•		•
	1802.1	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 32 mm.	2	P, PVD H, S		•		•
	1802.2	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 32 mm.	2	P, PVD H, S		•		•






	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1802.3	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 32 mm.	2	P, PVD H, S		●		●
	1802.4	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 32 mm.	2	P, PVD H, S		●		●
	1802.5	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 32 mm.	2	P, PVD H, S		●		●
	1802.6	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 35 mm.	2	S		●		●
	1802.10L	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 32 mm.	1	P, PVD H, S		●		●
	1802.10R	EXCALIBUR Like 1802.10L but RH version.	1	P, PVD H, S		●		●
	1802.11L	EXCALIBUR Stainless steel (AISI 304) handle with brass bushings and pre-mounted stainless steel set screws. Diameter 32 mm.	1	P, PVD H, S		●		●
	1802.11R	EXCALIBUR Like 1802.11L but RH version.	1	P, PVD H, S		●		●
	1810.1	Single fastener. Consisting of: 2 galvanized set screws M8x45, 2 bushings M8, 2 extra-large nuts.	1			●		●
	1810.2	Single fastener with counter-plate. Consisting of: 2 galvanized set screws M8x45, 2 bushings M8, 2 counter-plates with spring.	1			●		●




PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	1811.1	Double fastener. Consisting of: 2 threaded bars M8x100, 4 bushings M8. For door profiles with section from 30 to 60 mm.	1			●		●
	3000.4	RIBANTA 4 (patented) 4-point locking device for turn-first function, vertical fulcrum. Basic kit with standard arm in stainless steel 304, corner drive and locking points in black galvanized zamak, 7 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3000.5	RIBANTA 4 Like 3000.4 but with short arm (5 bushings).	5		●		●	
	3000.6	RIBANTA 4 (patented) 4-point locking device for turn-first function, corner drive fulcrum. Basic kit with standard arm in stainless steel 304, corner drive and locking points in black galvanized zamak, 8 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3000.7	RIBANTA 4 Like 3000.6 but with short arm (5 bushings).	5		●		●	
	3000.731	(patented) Kit of RH hinges in zamak and aluminium, 1 countersunk head screw M5x8, 4 countersunk oval head screws M5x10, 1 countersunk head screw M5x16 and 1 countersunk head screw Ø 3,9x13 in stainless steel 304. Casement max. weight 100 Kg.	5	1013, 1015, 7035, 8019, 9001, 9005, 9010, 9016, BL10, BR4, BR5, BR801, C, GR217, GR606, HL, SILV	●		●	
	3000.732	(patented) Transformation kit in zamak, for RIBANTA 4 LH version.	5	1013, 1015, 8019, 9001, 9005, 9010, BL10, BR801, C, GR217, GR606, RD501, SILV, WT005	●		●	
	3000.739	Non-handed hinge Kit for RIBANTA 4. Casement max. weight 100 Kg.	5	1013, 1015, 1247, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR4, BR5, BR801, BW21, C, GR217, GR606, HL, PVD H, PVD X, RD501, SILV, WT005	●		●	
	3000.742	LH transformation hinge pivot for tilt and turn, for art. 3000.6/.7.	5	1013, 1015, 8019, 9001, 9005, 9010, BL10, BR4, BR5, BR801, C, GR217, GR606, HL, SILV	●		●	
	3000.751	RIBANTA 4 Not preassembled standard arm for turn-first function, in stainless steel 304, not-galvanized zamak, aluminium rod, rod-connection locking piece in black galvanized zamak, screws in stainless steel 304.	5		●		●	
	3000.771	RIBANTA 4 Like 3000.751 but 20 pcs. pack.	20		●		●	
	3000.800	Locking piece (only for tilt and turn + semi-fixed casement), alternative to the upper bolt.	40		●		●	
	3000.820	Kit for vertical supplementary locking points in black galvanized zamak, 2 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3000.830	(patented) Clamp in hinge kit for casement alongside RIBANTATRE in zamak, aluminium and stainless steel 430, 2 countersunk head screws M5x8, 4 countersunk head screws M5x12, 2 countersunk head screws M5x16 and 4 countersunk head screws Ø 4,2x13 in stainless steel 304. To be used with art. 3000.739.	5	1013, 1015, 1247, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR4, BR5, BR801, BW21, C, GR217, GR606, HL, PVD H, PVD X, RD501, SILV, WT005	●		●	





	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3001	RIBANTA 4 (patented) 4-point locking device for tilt-first function and with vertical lateral fulcrum. Basic kit with standard arm in stainless steel 430, corner drive and locking points in black galvanized zamak, 7 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3001.1	RIBANTA 4 Like 3001 but with short arm (5 bushings).	5		●		●	
	3001.6	RIBANTA 4 (patented) 4-point locking device for tilt-first function and with corner drive fulcrum. Basic kit with standard arm in stainless steel 304, corner drive and locking points in black galvanized zamak, 8 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3001.7	RIBANTA 4 Like 3001.6 but with short arm (5 bushings).	5		●		●	
	3001.10	RIBANTA 4 (patented) 4-point locking device for tilt-first function and with vertical lateral fulcrum, left hand. Basic kit with standard arm in stainless steel 430, corner drive and locking points in black galvanized zamak, 7 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3001.11	RIBANTA 4 Like 3001.10 but with short arm (5 bushings).	5		●		●	
	3001.751	RIBANTA 4 Not preassembled standard arm for tilt-first function, in stainless steel 304, not-galvanized zamak, aluminium rod, rod-connection locking piece in black galvanized zamak, screws in stainless steel 304.	5		●		●	
	3001.771	RIBANTA 4 Like 3001.751 but 20 pcs. pack.	20		●		●	
	3010	RIBANTA INCANTO (pat.) 4-point locking device for turn-first function, corner drive fulcrum. Basic kit with standard arm in galvanized steel, RH concealed hinges made in black galvanized zamak and high resistance white galvanized steel, corner drive and locking points in black galvanized zamak, 9 nylon bushings Ø 6-8 mm, screws in stainless steel AISI 304.	5		●		●	
	3010.1	RIBANTA INCANTO Like 3010 but with left hinge.	5		●		●	
	3010.3	RIBANTA INCANTO Like 3010 but with short arm (7 bushings).	5		●		●	
	3010.4	RIBANTA INCANTO Like 3010.3 but with left hinge.	5		●		●	
	3010.820	Kit for vertical supplementary locking points in black galvanized zamak, 6 preassembled grub screws M5x12 in stainless steel 304	5		●		●	
	3011	RIBANTA INCANTO (pat.) 4-point locking device for tilt-first function, corner drive fulcrum. Basic kit with standard arm in galvanized steel, RH concealed hinges made in black galvanized zamak and high resistance white galvanized steel, corner drive and locking points in black galvanized zamak, 9 nylon bushings Ø 6-8 mm, screws in stainless steel AISI 304.	5		●		●	
	3011.1	RIBANTA INCANTO Like 3011 but with left hinge.	5		●		●	
	3011.3	RIBANTA INCANTO Like 3011 but with short arm (7 bushings).	5		●		●	
	3011.4	RIBANTA INCANTO Like 3011.3 but with left hinge.	5		●		●	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3020	(patented) Concealed hinges kit for RIBANTA INCANTO secondary casement in zamak and high resistance white galvanized steel. Casement max weight of 80 Kg.	5		●		●	
	3040.701	(patented) RH clamp in hinge kit for RIBANTA 4, in zamak and aluminium, preassembled counterplates in stainless steel 304 and stainless steel 430, 1 countersunk head screw Ø 3.9x13, 1 countersunk head screw M5x8, 2 countersunk oval head screws M5x10, 1 preassembled grub screw M5x12 and 1 preassembled grub screw M5x6 in stainless steel 304, 2 preassembled countersunk oval head screws M5x10 and 1 preassembled countersunk head screws M5x16 in stainless steel 304 with unscrewing painting protection. Casement max weight of 100 Kg (70 Kg without supplementary screws included).	5	1013, 1015, 7035, 8019, 9001, 9005, 9010, 9016, BL10, BR5, BR801, C, GR217, GR606, HL, PVD X, SILV	●		●	
	3040.709	(patented) Non-handed clamp in hinge kit for RIBANTA 4, in zamak and aluminium, preassembled counterplates in stainless steel 304 and stainless steel 430, 1 countersunk head screw Ø 3.9x13, 1 countersunk head screw M5x8, 2 countersunk oval head screws M5x10, 1 preassembled grub screw M5x12 and 1 preassembled grub screw M5x6 in stainless steel 304, 2 preassembled countersunk oval head screws M5x10 and 1 preassembled countersunk head screws M5x16 in stainless steel 304 with unscrewing painting protection. Casement max weight of 100 Kg (70 Kg without supplementary screws included).	5	1013, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, HL, PVD H, PVD X, SILV, WT005	●		●	
	3040.721	Like 3040.701 but 20 pcs. pack.	20	1013, 9005, 9010	●		●	
	3040.729	Like 3040.709 but 20 pcs. pack.	20	1013, 9005, 9010	●		●	
	3040.734	(patented) LH clamp in hinge kit for RIBANTA 4, in zamak and aluminium, preassembled counterplates in stainless steel 304 and stainless steel 430, 1 countersunk head screw Ø 3.9x13, 1 countersunk head screw M5x8, 2 countersunk oval head screws M5x10, 1 preassembled grub screw M5x12 and 1 preassembled grub screw M5x6 in stainless steel 304, 2 preassembled countersunk oval head screws M5x10 and 1 preassembled countersunk head screws M5x16 in stainless steel 304 with unscrewing painting protection. Casement max weight of 100 Kg (70 Kg without supplementary screws included).	5	9005, 9010, C, SILV	●		●	
	3040.750	RIBANTA 4 Preassembled standard arm for turn-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		●		●	
	3040.752	RIBANTA 4 Not preassembled short arm for turn-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		●		●	
	3040.770	RIBANTA 4 Like 3040.750 but 20 pcs. pack.	20		●		●	
	3040.772	RIBANTA 4 Like 3040.752 but 20 pcs. pack.	20		●		●	
	3040.830	(patented) Clamp in hinge kit for casement alongside RIBANTA 4 in zamak, aluminium and stainless steel 430, 2 countersunk head screws M5x8, 4 countersunk head screws M5x12, 2 countersunk head screws M5x16 and 4 countersunk head screws Ø 4,2x13 in stainless steel 304. To be used with art. 3040.709.	5	1013, 1015, 1247, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, HL, PVD H, PVD X, RD501, SILV, WT005	●		●	





	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3041.2	(patented) Basic kit for RIBANTA 4 tilt-first function, RH vertical lateral fulcrum and adjustable locking points in black galvanized zamak, 7 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3041.3	Like 3041.2 but LH version.	5		●		●	
	3041.22	Like 3041.2 but 20 pcs. pack.	20		●		●	
	3041.750	RIBANTA 4 Preassembled standard arm for tilt-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		●		●	
	3041.752	RIBANTA 4 Not preassembled short arm for tilt-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		●		●	
	3041.770	RIBANTA 4 Like 3041.750 but 20 pcs. pack.	20		●		●	
	3041.772	RIBANTA 4 Like 3041.752 but 20 pcs. pack.	20		●		●	
	3100	RIBANTATRE 150 (patented) 4-point locking device for turn-first function, corner drive fulcrum. Basic kit with standard arm in stainless steel 304, corner drives and adjustable locking points in black galvanized zamak, 8 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3100.1	RIBANTATRE 150 Like 3100 but with short arm (5 bushings).	5		●		●	
	3100.2	RIBANTATRE 150 NO CMP	5		●		●	
	3100.3	RIBANTATRE 150 Like 3100.2 but with short arm (5 bushings).	5		●		●	
	3100.701	(patented) Clamp in hinge kit for RIBANTATRE 150 in zamak, aluminium and stainless steel 430, 4 countersunk head screws Ø 4,2x13, 4 countersunk head M5x8, 2 countersunk head M5x12, 2 countersunk head M5x16 in stainless steel 304. Casement max weight of 150 Kg (100 Kg without supplementary screws included).	5	1013, 1015, 1247, 3001, 3003, 6005, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR4, BR5, BR801, BW21, C, GR217, GR606, GREY, HL, PVD H, PVD X, RD501, SILV, WT005	●		●	
	3100.751	RIBANTATRE 150 Not preassembled standard arm for turn-first function, in stainless steel 304, not-galvanized zamak, aluminium rod, rod-connection locking piece in black galvanized zamak, screws in stainless steel 304.	5		●		●	
	3100.771	RIBANTATRE 150 Like 3100.751 but 20 pcs. pack.	20		●		●	
	3100.800	Supplementary arm in stainless steel, zamak and nylon, 2 self-tapping countersunk head screws Ø 4,2x13 in galvanized steel.	5		●		●	
	3100.821	Locking piece in black galvanized zamak, 1 cup in low density polyethylene (LDPE), 1 bushing Ø 6-Ø 8 mm.	40		●		●	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3100.830	(patented) Clamp in hinge kit for casement alongside RIBANTATRE in zamak, aluminium and stainless steel 430, 2 countersunk head screws M5x8, 4 countersunk head screws M5x12, 2 countersunk head screws M5x16 and 4 countersunk head screws Ø 4,2x13 in stainless steel 304.	5	1013, 1015, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR4, BR5, BR801, BW21, GR217, GR606, HL, PVD H, PVD X, RD501, SILV, WT005	•		•	
	3101	RIBANTATRE 150 4-point locking device for tilt-first function, corner drive fulcrum. Basic kit with standard arm in stainless steel 304, corner drive and adjustable locking points in black galvanized zamak, 8 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		•		•	
	3101.1	RIBANTATRE 150 Like 3101 but with short arm (5 bushings).	5		•		•	
	3101.751	RIBANTATRE 150 Not preassembled standard arm for tilt-first function, in stainless steel 304, not-galvanized zamak, aluminium rod, rod-connection locking piece in black galvanized zamak, screws in stainless steel 304.	5		•		•	
	3101.771	RIBANTATRE 150 Like 3101.751 but 20 pcs. pack.	20		•		•	
	3101.800	Supplementary arm tilt-first function in stainless steel, zamak and nylon, 2 self-tapping countersunk head screws Ø 4,2x13 in galvanized steel.	5		•		•	
	3150	(patented) Basic kit for turn-first function, corner drive fulcrum and adjustable locking points in black galvanized zamak, 8 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		•		•	
	3150.2	(patented) Basic kit for turn-first function, vertical fulcrum and adjustable locking points in black galvanized zamak, 7 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		•		•	
	3150.20	Like 3150 but 20 pcs. pack.	20		•		•	
	3150.22	Like 3150.2 but 20 pcs. pack.	20		•		•	
	3150.701	(patented) Clamp in hinge kit for RIBANTATRE 150 in zamak and aluminium, preassembled counterplates in stainless steel 304, 4 countersunk head screws Ø 4,2x13, 4 countersunk head screws M5x8, 2 countersunk head screws M5x12 and 1 grub screw M5x6 in stainless steel 304, 2 preassembled countersunk head screws M5x16 and 2 preassembled countersunk head screws M5x9 in stainless steel 304 with unscrewing painting protection. Casement max weight of 150 Kg (100 Kg without supplementary screws included).	5	1013, 1015, 1247, 3001, 6005, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR51, GR606, HL, PVD H, PVD X, SILV, WT005	•		•	
	3150.721	Like 3150.701 but 20 pcs. pack.	20	1013, 9005, 9010	•		•	
	3150.750	RIBANTATRE 150 Preassembled standard arm for turn-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		•		•	



	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3150.752	RIBANTATRE 150 Not preassembled short arm for turn-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		●		●	
	3150.770	RIBANTATRE 150 Like 3150.750 but 20 pcs. pack.	20		●		●	
	3150.772	RIBANTATRE 150 Like 3150.752 but 20 pcs. pack.	20		●		●	
	3150.800	Supplementary arm for turn-first function, in stainless steel 304, black galvanized zamak and black nylon, preanodized aluminium rod, 2 cap screws Ø 4,2x13 in stainless steel 304.	5		●		●	
	3150.830	(patented) Clamp in hinge kit in zamak and aluminium for casement alongside RIBANTATRE 150, preassembled counterplates in stainless steel 304, 4 countersunk head screws Ø 4.2x13, 4 countersunk head screws M5x12 and 1 grub screw M5x6 in stainless steel 304, 2 preassembled countersunk head screws M5x16 and 2 preassembled countersunk head screws M5x9 in stainless steel 304 with unscrewing painting protection.	5	1013, 1015, 7032, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, HL, PVD H, PVD X, SILV, WTO05	●		●	
	3151	(patented) Basic kit for tilt-first function, corner drive fulcrum and adjustable locking points in black galvanized zamak, 6 nylon bushings Ø 6-Ø 8 mm, screws in stainless steel 304.	5		●		●	
	3151.20	Like 3151 but 20 pcs. pack.	20		●		●	
	3151.750	RIBANTATRE 150 Preassembled standard arm for tilt-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		●		●	
	3151.752	RIBANTATRE 150 Not preassembled short arm for tilt-first function, in stainless steel 304, black galvanized zamak, preanodized aluminium rod, screws in stainless steel 304.	5		●		●	
	3151.770	RIBANTATRE 150 Like 3151.750 but 20 pcs. pack.	20		●		●	
	3151.772	RIBANTATRE 150 Like 3151.752 but 20 pcs. pack.	20		●		●	
	3151.800	Supplementary arm for tilt-first function, in stainless steel 304, black galvanized zamak and black nylon, 2 preanodized aluminium rods, 2 cap screws Ø 4,2x13 in stainless steel 304.	5		●		●	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3200.L	RIBANTA 5 (patented) Left vertical fulcrum Kit, turn-first function, in white galvanized zamak and black nylon, pre-mounted screw in stainless steel 304 and 430, left hinge support in stainless steel 304, left pin in stainless steel 201 with pre-mounted counterplate in stainless steel 430 and pin in galvanized steel, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	5		●		●	
	3200.R	RIBANTA 5 Like 3200.L but right hand.	5		●		●	
	3200.2L	RIBANTA 5 (patented) Left horizontal fulcrum Kit, turn-first function, in white galvanized zamak and black nylon, pre-mounted screw in stainless steel 304 and 430, left hinge support in stainless steel 304, left pin in stainless steel 201 with pre-mounted counterplate in stainless steel 430 and pin in galvanized steel, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	5		●		●	
	3200.2R	RIBANTA 5 Like 3200.2L but right hand.	5		●		●	
	3200.3L	RIBANTA 5 (patented) Left horizontal fulcrum Kit, fixed height of handle to 300 mm, turn-first function, in white galvanized zamak and black nylon, pre-mounted screw in stainless steel 304 and 430, left hinge support in stainless steel 304, left pin in stainless steel 201 with pre-mounted counterplate in stainless steel 430 and pin in galvanized steel, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	5		●		●	
	3200.3R	RIBANTA 5 Like 3200.3L but RH version.	5		●		●	
	3200.5L	RIBANTA 5 (patented) Left vertical fulcrum Kit, turn-first function, in white galvanized zamak and black nylon, pre-mounted screw in stainless steel 304 and 430 (without support and hinge pivot).	5		●		●	
	3200.5R	RIBANTA 5 Like 3200.5L but RH version.	5		●		●	
	3200.20L	RIBANTA 5 (patented) Left vertical fulcrum Kit, turn-first function, in white galvanized zamak and black nylon, pre-mounted screw in stainless steel 304 and 430.	20		●		●	
	3200.20R	RIBANTA 5 Like 3200.20L but right hand.	20		●		●	
	3200.22L	RIBANTA 5 (patented) Left horizontal fulcrum Kit, turn-first function, in white galvanized zamak and black nylon, pre-mounted screw in stainless steel 304 and 430.	20		●		●	
	3200.22R	RIBANTA 5 Like 3200.22L but right hand.	20		●		●	
	3200.600L	(patented) Left lateral closing Kit including: handle connection piece, 2 locking pieces (RH+LH) and 2 adjustable keepers in white galvanized zamak, pre-mounted screws made of 304 and 430 stainless steel.	40		●		●	

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3200.600R	Like 3200.600L but RH version.	40		●		●	
	3200.605L	(patented) Left terminal locking piece in white galvanized zamak, adjustable keeper, premounted screws made of 304 and 430 stainless steel.	40		●		●	
	3200.605R	Like 3200.605L but right hand.	40		●		●	
	3200.612	Upper and lower corner device kit in white zamak and nylon, stainless steel 304 and 430 screws, preassembled.	5		●		●	
	3200.615L	Telescopic rod and RH closing point in white galvanized zamak and stainless steel 304 screws, preassembled.	5		●		●	
	3200.615R	Like 3200.615L but right hand.	5		●		●	
	3200.700L	Left bottom hinge support (weight capacity 170 Kg) in stainless steel 304.	5		●		●	
	3200.700R	Like 3200.700L but RH version.	5		●		●	
	3200.701	RIBANTA 5 (patented) Non-handed hinge kit (weight capacity 170 Kg) in aluminum and zamak, premounted upper pin and counterplate in stainless steel 430, lower pin in galvanized steel with premounted stainless steel grub screw, premounted nylon bushing and adjustment grub screw, 2 socket flat head screws M5x12 in stainless steel premounted on lower window leaf, 1 grub screw M5x6, 1 socket flat head screw M5x8 and 2 self-forming countersunk head screws M5x18 in stainless steel 304.	5	1013, 1015, 1247, 3001, 6005, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, GREY, PVD H, PVD X, SILV, WT005	●		●	
	3200.708L	RIBANTA 5 (patented) Left reinforcement kit for hinge 3000.709 (upper part), weight capacity 140 Kg, in zamak, pin in stainless steel 430, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	5	1013, 1015, 1247, 3001, 6005, 7035, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, GREY, PVD H, PVD X, SILV, WT005	●		●	
	3200.708R	RIBANTA 5 Like 3200.708L but right hand.	5	1013, 1015, 1247, 3001, 6005, 7035, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, GREY, PVD H, PVD X, SILV, WT005	●		●	
	3200.709	RIBANTA 5 (patented) Non-handed hinge kit (weight capacity 110 Kg) in aluminum, premounted upper pin and counterplate in stainless steel 43, premounted nylon bushing and adjustment grub screw, 2 socket flat head screws M5x12 in stainless steel mounted on lower window leaf, 1 socket flat head screw M5x8 in stainless steel 304, nylon pin covers.	5	1013, 1015, 1247, 3001, 6005, 7035, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, GREY, HL, PVD H, PVD X, SILV, WT005	●		●	


PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3200.710L	Left lower support and pin for secondary leaf hinge (weight capacity 110-140 Kg), in stainless steel 304, left pin in stainless steel 201 with premounted counterplate in stainless steel 430 and pin in galvanized steel, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	5		●		●	
	3200.710R	Like 3200.710L but right hand.	5		●		●	
	3200.720L	Like 3200.700L but 20 pcs. pack.	20		●		●	
	3200.720R	Like 3200.720L but RH version.	20		●		●	
	3200.721	RIBANTA 5 Like 3200.701 but 20 pcs. pack.	20	1013, 9005, 9010, C, SILV	●		●	
	3200.729	RIBANTA 5 Like 3200.709 but 20 pcs. pack.	20	1013, 9005, 9010, C, SILV	●		●	
	3200.730L	Like 3200.710L but 20 pcs. pack.	20		●		●	
	3200.730R	Like 3200.730L but right hand.	20		●		●	
	3200.750L	RIBANTA 5 (patented) Left short arm, turn-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304, pre-oxidized aluminum rod divided into millimetres.	5		●		●	
	3200.750R	RIBANTA 5 Like 3200.750L but right hand.	5		●		●	
	3200.751L	RIBANTA 5 (patented) Left standard arm, turn-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted rod and rod divided into millimetres in pre-oxidized aluminum.	5		●		●	
	3200.751R	RIBANTA 5 Like 3200.751L but right hand.	5		●		●	
	3200.752L	RIBANTA 5 (patented) Left long arm, turn-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted pre-oxidized aluminum rod and telescopic pinion in white galvanized zamak.	5		●		●	
	3200.752R	RIBANTA 5 Like 3200.752L but right hand.	5		●		●	
	3200.770L	RIBANTA 5 (patented) Left short arm, turn-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304, pre-oxidized aluminum rod divided into millimetres.	20		●		●	
	3200.770R	RIBANTA 5 Like 3200.770L but right hand.	20		●		●	






	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3200.771L	RIBANTA 5 (patented) Left standard arm, turn-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted rod and rod divided into millimetres in pre-oxidized aluminum.	20		●		●	
	3200.771R	RIBANTA 5 Like 3200.771L but right hand.	20		●		●	
	3200.772L	RIBANTA 5 (patented) Left long arm, turn-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted pre-oxidized aluminum rod telescopic pinion in white galvanized zamak.	20		●		●	
	3200.772R	RIBANTA 5 Like 3200.772L but right hand.	20		●		●	
	3200.800L	RIBANTA 5 (patented) Left additional arm, turn-first function, in stainless steel 304, white galvanized zamak and black nylon, premounted screw in stainless steel 304 and 430.	5		●		●	
	3200.800R	RIBANTA 5 Like 3200.800L but right hand.	5		●		●	
	3200.801	Anti-slam device (right + left) in red nylon for standard and long arm.	40		●		●	
	3200.802	Anti-slam device (right + left) in red nylon for supplementary arm.	40		●		●	
	3200.805L	(patented) Left locking piece and adjustable keeper in white galvanized zamak, premounted screws in stainless steel 304, 1 premounted clip in black nylon.	40		●		●	
	3200.805R	Like 3200.805L but right hand.	40		●		●	
	3200.809	Hinge kit in aluminium for second leaf, pre-assembled pins and counterplates in stainless steel 430, black nylon bushings, 4 socket head cap screws M5x16 and 2 special countersunk oval socket flat head screws M5x10 in stainless steel 430, pre-assembled. Weight capacity 80 Kg.	5	1013, 1015, 1247, 6005, 7035, 8017, 8019, 9001, 9005, 9010, 9016, B.SA, BL10, BR5, BR801, BW21, C, GR217, GR606, HL, PVD H, PVD X, SILV, WT005	●		●	
	3200.810	(patented) Intermediate closing point in white galvanized zamak, premounted screws in stainless steel 304 and 430, and adjustable locking piece.	40		●		●	
	3200.820L	(patented) Left kit for 6 closing points in white galvanized zamak, premounted screws in stainless steel 304 and 430.	5		●		●	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3200.820R	Like 3200.820L but RH version.	5		●		●	
	3200.825L	(patented) Left Kit for 8 closing points in white galvanized zamak, premounted screws in stainless steel 304 and 430.	5		●		●	
	3200.825R	Like 3200.825L but RH version.	5		●		●	
	3200.829	Like 3200.809 but 20 pcs. pack.	20	1013, 9005, 9010	●		●	
	3200.835	Anti-burglar device in stainless steel 304, 1 socket flat head screw M4x8 in stainless steel 304, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	20		●		●	
	3200.840L	(patented) Left upper adjustable support for secondary leaf hinge in white galvanized zamak and stainless steel arm, premounted stainless steel screw 304.	5		●		●	
	3200.840R	Like 3200.840L but right hand.	5		●		●	
	3200.860L	(patented) Left upper support for secondary leaf hinge in white galvanized zamak and stainless steel arm, premounted stainless steel screw 304.	20		●		●	
	3200.860R	Like 3200.840R but 20 pcs. pack.	20		●		●	
	3200.704L	LH handle connection piece in white galvanized zamak, preassembled grub screw in stainless steel 304.	40		●		●	
	3200.704R	Like 3200.704L but right hand.	40		●		●	
	3201.L	RIBANTA 5 (patented) Left vertical lateral fulcrum Kit, tilt-first function, in white galvanized zamak and black nylon, premounted screw in stainless steel 304 and 430, left hinge support in stainless steel 304, left pin in stainless steel 201 with premounted counterplate in stainless steel 430 and pin in galvanized steel, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	5		●		●	
	3201.R	RIBANTA 5 Like 3201.L but right hand.	5		●		●	
	3201.2L	RIBANTA 5 (patented) Left horizontal fulcrum Kit, tilt-first function, in white galvanized zamak and black nylon, premounted screw in stainless steel 304 and 430, left hinge support in stainless steel 304, left pin in stainless steel 201 with premounted counterplate in stainless steel 430 and pin in galvanized steel, 1 self-forming countersunk head screw M5x18 in stainless steel 304.	5		●		●	

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3201.2R	RIBANTA 5 Like 3201.2L but right hand.	5		●		●	
	3201.22L	RIBANTA 5 (patented) Left horizontal fulcrum Kit, tilt-first function, in white galvanized zamak and black nylon, premounted screw in stainless steel 304 and 430.	20		●		●	
	3201.22R	RIBANTA 5 Like 3201.22L but right hand.	20		●		●	
	3201.750L	RIBANTA 5 (patented) Right short arm, tilt-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304, pre-oxidized aluminum rod divided into millimetres.	5		●		●	
	3201.750R	RIBANTA 5 Like 3201.750L but right hand.	5		●		●	
	3201.751L	RIBANTA 5 (patented) Left standard arm, tilt-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted rod and rod divided into millimetres in pre-oxidized aluminum.	5		●		●	
	3201.751R	RIBANTA 5 Like 3201.751L but right hand.	5		●		●	
	3201.752L	RIBANTA 5 (patented) Left long arm, tilt-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted pre-oxidized aluminum rod and telescopic pinion in white galvanized zamak.	5		●		●	
	3201.752R	RIBANTA 5 Like 3201.752L but right hand.	5		●		●	
	3201.770L	RIBANTA 5 (patented) Right short arm, tilt-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304, pre-oxidized aluminum rod divided into millimetres.	20		●		●	
	3201.770R	RIBANTA 5 Like 3201.770L but right hand.	20		●		●	
	3201.771L	RIBANTA 5 (patented) Left standard arm, tilt-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted rod and rod divided into millimetres in pre-oxidized aluminum.	20		●		●	
	3201.771R	RIBANTA 5 Like 3201.771L but right hand.	20		●		●	
	3201.772L	RIBANTA 5 (patented) Left long arm, tilt-first function, in white galvanized zamak, black nylon, stainless steel 201 and 304, premounted screw in stainless steel 304 and 430, premounted pre-oxidized aluminum rod and telescopic pinion in white galvanized zamak.	20		●		●	

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	3201.772R	RIBANTA 5 Like 3201.772L but right hand.	20		●		●	
	3201.800L	RIBANTA 5 (patented) Left supplementary arm, tilt-first function, in stainless steel 304, white galvanized zamak and black nylon, premounted screw in stainless steel 304 and 430.	5		●		●	
	3201.800R	RIBANTA 5 Like 3201.800L but right hand.	5		●		●	
	6000.1/1200	BERNINI (patented) Horizontal non-handed panic bar with 1 locking point in zamak and galvanised steel. Complete with: latch bolt in nickel plated zamak, counterplates in galvanised steel, 1200 bar in painted steel, 1 keeper + 3 spacers in painted zamak, 8 countersunk head screws Ø 4.2x13 in black galvanised steel, 2 cap screws Ø 4.2x19 in black galvanised steel, 16 countersunk head screws M4x5 in black galvanised steel. For doors with a clear width of 800 to 1240 mm and a max. height of 2450 mm.	1	3001, 6029, 9005, GREY		●		●
	6000.99/120	BERNINI Like 6000.1/1200 but with supports and bar same finish.	1	1013, 9005, 9010, GREY, SILV		●		●
	6000.2/1200	BERNINI (patented) Vertical rod non-handed panic bar with 2 locking points in zamak and galvanised steel. Complete with: counterplates in galvanised steel, 1200 bar in painted steel, 1 floor-mounted keeper in stainless steel, 1 black nylon insert, 1 top rod + 1 bottom rod in aluminium, 1 rod cover in painted aluminium 1395 mm, 1 rod cover in painted aluminium 1037 mm, 2 adjustable plugs in black galvanised zamak, 1 keeper + 3 spacers in painted zamak, 8 countersunk head screws Ø 4.2x13 in black galvanised steel, 2 cap screws Ø 4.2x19 in black galvanised steel, 4 cap screws Ø 4.2x9.5 in black galvanised steel, 22 countersunk head screws M4x5 in black galvanised steel. For doors with a clear width of 800 to 1240 mm and a max. height of 2450 mm.	1	3001, 6029, 9005, GREY		●		●
	6000.98/120	BERNINI Like 6000.2/1200 but with supports and bar same finish.	1	1013, 9005, 9010, GREY, SILV		●		●
	6000.3/1200	BERNINI (patented) Vertical rod non-handed panic bar with 3 locking points in zamak and galvanized steel. Complete with: latch bolt in nickel plated zamak, counterplates in white galvanized steel, 1200 bar in painted steel, 1 top rod + 1 bottom rod in aluminium, 1 1395 mm rod cover in painted aluminium, 1 1037 mm rod cover in painted aluminium, 2 adjustable plugs in black galvanised zamak, 3 keepers + 9 spacers in painted zamak, 10 countersunk head screws Ø 3.9x13 in white galvanised steel, 8 countersunk head screws Ø 4.2x13 in black galvanised steel, 6 cap screws Ø 4.2x19 in black galvanised steel, 28 countersunk head screws Ø M4x5 in black galvanised steel. For doors with a clear width of 800 to 1240 mm and a max. height of 2450 mm.	1	3001, 6029, GREY		●		●
	6000.97/120	BERNINI Like 6000.3/1200 but with supports and bar same finish.	1	1013, 9005, 9010, GREY, SILV		●		●
	6000.701	BERNINI (patented) Kit with horizontal non-handed supports, one locking point in painted zamak and galvanised steel. Complete with: latch bolt in nickel plated zamak, counterplates in galvanised steel, 1 keeper + 3 spacers in painted zamak, right and left nylon bar caps, 8 countersunk head screws Ø 4.2x13 in galvanised steel, 2 cap screws Ø 4.2x19 in galvanised steel, 16 countersunk head screws M4x5 in black galvanised steel (for finishes 9006/9010: 8 countersunk head screws M4x5 in galvanised steel + 8 countersunk head screws M4x6 in stainless steel).	1	9005, 9010, GREY, SILV		●		●







	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	6000.702	BERNINI (patented) Kit with non-handed vertical supports, two locking points in painted zamak and galvanised steel. Complete with: galvanised steel counterplates, right and left nylon bar caps, 8 countersunk head screws Ø 4.2x13 in galvanised steel, 16 countersunk head screws M4x5 in galvanised steel (for finishes 9006/9010: 8 countersunk head screws M4x5 in galvanised steel + 8 countersunk head screws M4x6 in stainless steel).	1	9005, 9010, GREY, SILV		●		●
	6000.703	BERNINI (patented) Kit with non-handed supports, three locking points in painted zamak and galvanised steel. Complete with: latch bolt in nickel plated zamak, counterplates in galvanised steel, 1 keeper + 3 spacers in painted zamak, right and left nylon bar caps, 8 countersunk head screws Ø 4.2x13 in galvanised steel, 2 cap screws Ø 4.2x19 in galvanised steel, 16 countersunk head screws M4x5 in black galvanised steel (for finishes 9006/9010: 8 countersunk head screws M4x5 in galvanised steel + 8 countersunk head screws M4x6 in stainless steel).	1	9005, 9010, GREY, SILV		●		●
	6000.730	(patented) Kit with top / bottom latch bolts in painted zamak and galvanised steel, nickel plated latch bolt. Including: fastening counterplates in galvanised steel, 1 floor-mounted keeper in stainless steel + 1 black nylon insert, 2 adjustable plugs in galvanised zamak, 1 keeper + 3 spacers in painted zamak, 6 countersunk head screws Ø 3.9x13 in white galvanised steel, 4 cap screws Ø 4.2x9.5 in galvanised steel, 2 cap screws Ø 4.2x19 in galvanised steel, 6 countersunk head screws M4x5 in white galvanised steel (for finishes 9006/9010: 4 countersunk head screws M4x5 in black galvanised steel + 2 countersunk head screws M4x6 in stainless steel).	1	1013, 9005, 9010, GREY, PVD X, SILV		●		●
	6000.735	(patented) Kit with top/side latch bolts in painted zamak and galvanised steel, nickel plated latch bolt. Including: fastening counterplates in galvanised steel, 2 adjustable plugs in galvanised zamak, 2 keepers + 6 spacers in painted zamak, 8 countersunk head screws Ø 3.9x13 in white galvanised steel, 2 cap screws Ø 4.2x9.5 and 4 cap screws Ø 4.2x19 in galvanised steel, 9 countersunk head screws M4x5 in white galvanised steel (for finishes 9006/9010: 6 countersunk head screws M4x5 in black galvanised steel + 3 countersunk head screws M4x6 in stainless steel).	1	9005, 9010, GREY, SILV		●		●
	6000.740	(patented) Kit with side latch bolts in painted zamak and galvanised steel, nickel plated latch bolt. Including: fastening counterplates in galvanised steel, 2 keepers + 6 spacers in painted zamak, 2 adjustable through-guides in galvanised zamak, 10 countersunk head screws Ø 3.9x13 in galvanised steel, 4 cap screws Ø 4.2x19 in galvanised steel, 12 countersunk head screws M4x5 in black galvanised steel (for finishes 9006/9010: 8 countersunk head screws M4x5 in galvanised steel + 4 countersunk head screws M4x6 in stainless steel).	1	9005, 9010, GREY, SILV		●		●
	6000.751	(patented) Support for horizontal latching device with one push-pad in painted zamak and galvanised steel, nickel plated latch bolt. Complete with: fastening counterplates in galvanised steel, 93 mm painted steel bar, 1 keeper + 3 spacers in painted zamak, right and left nylon bar caps, 4 countersunk head screws Ø 4.2x13 in galvanised steel, 2 cap screws Ø 4.2x19 in galvanised steel, 8 countersunk head screws M4x5 in galvanised steel.	1	1013, 9005		●		●
	6000.752	(patented) Support for vertical latching device, push-pad in painted zamak and galvanised steel. Complete with: galvanised steel fastening counterplate, 93 mm painted steel bar, nylon right and left bar caps, 4 countersunk head screws Ø 4.2x13 in galvanised steel, 8 countersunk head screws M4x5 in galvanised steel.	1	1013, 9005, 9010, GREY, SILV		●		●









PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	6000.807	Kit made of 1 upper keeper and 3 spacers (1, 2, 4 mm) in white powder coated zamak for vertical closing, 2 self-tapping screws TC Ø 4.2x16, 2 self-tapping screws TC Ø 4.2x22 and 2 washers in galvanized steel.	20	9005, 9010, GREY, SILV		●		●
	6000.809	Kit made of 1 upper keeper and 3 spacers (1, 2, 4 mm) in white powder coated zamak for horizontal closing, 2 self-tapping screws TC Ø 4.2x16, 2 self-tapping screws TC Ø 4.2x22 and 2 washers in galvanized steel.	20	9005, 9010, GREY, SILV		●		●
	6000.810	Supplementary lateral locking device in painted zamak and galvanised steel, latch bolt in nickel plated zamak, counterplate in white galvanised steel, 1 keeper + 3 spacers in painted zamak, 4 countersunk head screws Ø 3.9x13 in white galvanised steel, 2 cap screws Ø 4.2x19 and 6 countersunk head screws M4x5 in black galvanised steel (for finishes 9006/9010: 4 countersunk head screws M4x5 in black galvanised steel + 2 countersunk head screws M4x6 in stainless steel).	1	9005, 9010, GREY, SILV		●		●
	6000.820	Electric strike with cover in painted zamak, bottom plate in galvanised steel, 4 cap screws Ø 3.9x25 in white galvanised steel, black nylon spacers. Electrical feed: 12 V CA.	1	9005, 9010, GREY, SILV		●		●
	6000.840	BERNINI Intermediate support in painted zamak, fastening counterplate in galvanised steel, 4 countersunk head screws Ø 4.2x13 in galvanised steel, 8 black galvanised countersunk head screws M4x5 (for finishes 9006/9010: 4 galvanised countersunk head screws M4x5 + 4 stainless steel countersunk head screws M4x6).	1	9005, 9010, SILV		●		●
	6000.870	External access device, handle only, in painted zamak and galvanised steel, painted die-cast aluminium grip, square spindle in galvanised steel, 1 socket head cap screw M5x30 in white galvanised steel + 2 countersunk head screws M5x80 in black galvanised steel.	1	9005, 9010, GREY, SILV				●
	6000.873	External access device, idle handle, in painted zamak and galvanised steel, handle grip in zamak, european-shaped cylinder with different key combinations, 3 nickel plated keys, squared spindle in white galvanised steel, 2 countersunk head screw M5x80 in galvanised steel.	1	9005, 9010, GREY, SILV				●
	6000.874	Like 6000.873 but with single key combination.	1	9005, 9010, GREY, SILV				●
	6000.875	External access device, idle handle, in painted zamak and galvanised steel, painted die-cast aluminium grip, European profile cylinder with different key combinations + 3 nickel plated keys, square spindle in white galvanised steel, 1 socket head cap screw M5x30 in white galvanised steel + 2 countersunk head screws M5x80 in black galvanised steel. With "cylinder unlocked key retention device".	1	9005, 9010, GREY, PVD X, SILV				●

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	6000.876	External access device, idle handle, in painted zamak and galvanised steel, painted die-cast aluminium grip, without cylinder, square spindle in galvanised steel, 1 socket head cap screw M5x30 in white galvanised steel + 2 countersunk head screws M5x80 in black galvanised steel. With "cylinder unlocked key retention device".	1	1013, 9005, 9010, GREY, PVD X, SILV				●
	6000.877	External access device, idle handle, in painted zamak and galvanised steel, painted die-cast aluminium grip, European profile cylinder with single key combination + 3 nickel plated keys, square spindle in galvanised steel, 1 socket head cap screw M5x30 in white galvanised steel + 2 countersunk head screws M5x80 in black galvanised steel. With "cylinder unlocked key retention device".	1	9005, 9010, GREY, SILV				●
	6000.880	Outside access device in painted zamak and galvanised steel, fixed handle with knob, European profile cylinder with different key combinations + 3 nickel plated keys, square spindle in galvanised steel, 2 countersunk head screws M5x80 in black galvanised steel. Preferably for use with the 1 locking point version.	1	9005, 9010, GREY, SILV				●
	6000.899	BERNINI external handles adapter kit to use for CIRCEO panic device. Complete with: fixing counterplates made of galvanized steel, handle rotation limiter device in galvanized zamak, 1 countersunk head screws M4x12 in galvanized steel.	20			●		●
	6100.1/1085	CELLINI (patented) Horizontal non-handed panic bar with 1 locking point in zamak and galvanized steel. Complete with: latch bolt in nickel plated zamak, counterplates in white galvanized steel, 1085 mm bar in painted aluminium complete with black nylon gasket for aesthetical reasons, 1 keeper + 3 spacers in painted zamak, 8 countersunk head screws Ø 4.2x13, 2 cap screws Ø 4.2x19, 12 countersunk head screws M4x5 and 2 countersunk head screws M4x16 in black galvanized steel, 4 grub screws M6x8 in white galvanized steel and 1 grub screw fitting jig in black nylon. For doors with a clear width of 800 to 1240 mm and a max. height of 2450 mm.	1	3001, 6029, 9005		●		●
	6100.99/108	CELLINI Like 6100.1/1085 but with supports and bar same finish.	1	9005, 9010, GREY		●		●
	6100.2/1085	CELLINI (patented) Vertical non-handed panic bar with 2 locking points in zamak and galvanized steel. Complete with: counterplates in white galvanized steel, 1085 mm bar in painted aluminium complete with black nylon gasket for aesthetical reasons, 1 floor-mounted keeper in stainless steel, 1 black nylon insert, 1 upper rod and 1 lower rod in aluminium, 1 rod cover 1395 mm and 1 rod cover 1037 mm in painted aluminium, 2 adjustable plugs in black galvanised zamak, 1 keeper + 3 spacers in painted zamak, 6 countersunk head screws Ø 3.9x13 in white galvanized steel, 8 countersunk head screws Ø 4.2x13, 2 cap screws Ø 4.2x19, 4 cap screws Ø 4.2x9.5, 18 countersunk head screws M4x5 and 2 countersunk head screws M4x16 in black galvanized steel, 4 grub screws M6x8 in white galvanized steel, 1 grub screw fitting jig in black nylon. For doors with a clear width of 800 to 1240 mm and a max. height of 2450 mm.	1	3001, 6029, 9005		●		●
	6100.98/108	CELLINI Like 6100.2/1085 but with supports and bar same finish.	1	9005, 9010, GREY, SILV		●		●




PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	6100.3/1085	CELLINI (patented) Vertical non-handed panic bar with 3 locking points in zamak and galvanized steel. Complete with: latch bolt in nickel plated zamak, counterplates in white galvanized steel, 1085 mm bar in painted aluminium complete with black nylon gasket for aesthetical reasons, 1 upper rod + 1 lower rod in aluminium, 1 rod cover 1395 mm and 1 rod cover 1037 mm in painted aluminium, 2 adjustable plugs in black galvanized zamak, 3 keepers + 9 spacers in painted zamak, 10 countersunk head screws Ø 3.9x13 in white galvanized steel, 8 countersunk head screws Ø 4.2x13, 6 cap screws Ø 4.2x19, 24 countersunk head screws M4x5 and 2 countersunk head screws M4x16 in black galvanized steel, 4 grub screws M6x8 in white galvanized steel, 1 grub screw fitting jig in black nylon. For doors with a clear width of 800 to 1240 mm and a max. height of 2450 mm.	1	3001, 6029		●		●
	6100.97/108	CELLINI Like 6100.3/1085 but with supports and bar same finish.	1	9005, 9010, GREY, SILV		●		●
	6100.701	CELLINI (patented) Kit with horizontal non-handed supports, one locking point in painted zamak and galvanized steel. Including: latch bolt in nickel plated zamak, counterplates and 4 grub screws M6x8 in white galvanized steel, 1 keeper + 3 spacers in painted zamak, 8 countersunk head screws Ø 4.2x13, 2 cap screws Ø 4.2x19, 12 countersunk head screws M4x5 and 2 countersunk head screws M4x16 in black galvanized steel, 1 grub screw fitting jig in black nylon (for finishes 9006/9010: 8 countersunk head screws M4x5 in black galvanized steel, 4 countersunk head screws M4x6 and 2 countersunk head screws M4x16 in stainless steel).	1	9005, 9010, PVD X, SILV		●		●
	6100.702	CELLINI (patented) Kit with vertical non-handed supports, two locking points in painted zamak and galvanized steel. Including: counterplates and 4 grub screws M6x8 in white galvanized steel, 8 countersunk head screws Ø 4.2x13, 12 countersunk head screws M4x5, 2 countersunk head screws M4x16 in black galvanized steel, 1 grub screw fitting jig in black nylon (for finishes 9006/9010: 8 countersunk head screws M4x5 in black galvanized steel, 4 countersunk head screws M4x6 and 2 countersunk head screws M4x16 in stainless steel).	1	9005, 9010, GREY, SILV		●		●
	6100.703	CELLINI (patented) Kit with non-handed supports, three locking points in painted zamak and galvanized steel. Including: latch bolt in nickel plated zamak, counterplates in white galvanized steel, 1 keeper + 3 spacers in painted zamak, 8 countersunk head screws Ø 4.2x13, 2 cap screws Ø 4.2x19, 12 countersunk head screws M4x5 and 2 countersunk head screws M4x16 in black galvanized steel, 4 grub screws M6x8 in white galvanized steel, 1 grub screw fitting jig in black nylon (for finishes 9006/9010: 8 countersunk head screws M4x5 in galvanized steel, 4 countersunk head screws M4x6 and 2 countersunk head screws M4x16 in stainless steel).	1	9005, 9010, GREY, PVD X, SILV		●		●
	F6.R	Aluminium cable-covering profile.	10	1013, 1015, 6005, 8017, 8019, 9005, 9010, 9016, B.SA, GR217, SILV			●	
	F7	NEWTON (patented) Adjustable fanlight opener for bottom hung casement in steel, zamak and nylon, polyester cable (3 m), screws in galvanized steel. Weight capacity: 80 Kg.	5	1013, 1015, 6005, 8017, 8019, 9005, 9010, 9016, B.SA, GR217, GREY, SILV			●	

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	KH	CIRCEO (patented) Reversible horizontal panic device in die-cast aluminium, zamak and steel, 2 cap screws Ø 4.2x13, 8 countersunk head screws Ø 4.2x13, 8 countersunk head screws M4x30 in galvanized steel. Complete with green bar 1180 mm and galvanized steel fixing counterplates. Max width of doors 1240 mm.	1			●		●
	KH.11	CIRCEO (patented) Reversible horizontal panic device without bar, in die-cast aluminium, zamak and steel, 2 cap screws Ø 4.2x13, 8 countersunk head screws Ø 4.2x13, 8 countersunk head screws M4x30 in galvanized steel. Max width of doors 1240 mm.	1			●		●
	KH.2	CIRCEO (patented) Non-handed vertical panic device in die-cast aluminium, zamak, steel and bronze, 2 countersunk head screws M4x8, 2 cap screws Ø 4,2x13, 12 countersunk head screws Ø4,2x13, 4 countersunk head screws Ø 4,2x38, 8 countersunk head screws M4x30 in galvanized steel. Complete with green bar 1180 mm, black painted upper rod 1250 mm, black painted lower rod 900 mm and galvanized steel fixing counterplates. Max width of doors 1240 mm and max height 2400 mm.	1			●		●
	KH.21	CIRCEO (patented) Non-handed vertical panic device, without bar, in die-cast aluminium, zamak, steel and bronze, 2 countersunk head screws M4x8, 2 cap screws Ø 4,2x13, 12 countersunk head screws Ø4,2x13, 4 countersunk head screws Ø 4,2x38, 8 countersunk head screws M4x30 in galvanized steel. Complete with black painted upper rod 1250 mm, black painted lower rod 900 mm and galvanized steel fixing counterplates. Max width of doors 1240 mm and max height 2400 mm.	1			●		●
	KH.3	CIRCEO (patented) Non-handed vertical panic handle with lateral closing, in die-cast aluminium, zamak and steel, 4 cap screws Ø 4,2x13, 16 countersunk head screws Ø 4,2x13, 16 countersunk head screws M4x30 in galvanized steel. Complete with green bar 1180 mm, black painted upper rod 1250 mm, black painted lower rod 900 mm and galvanized steel fixing counterplates. Max width of doors 1240 mm and max height 2400 mm.	1			●		●
	KH.31	CIRCEO (patented) Non-handed vertical panic handle with lateral closing, without bar, in die-cast aluminium, zamak and steel, 4 cap screws Ø 4,2x13, 16 countersunk head screws Ø 4,2x13, 16 countersunk head screws M4x30 in galvanized steel. Complete with black painted upper rod 1250 mm, black painted lower rod 900 mm and galvanized steel fixing counterplates. Max width of doors 1240 mm and max height 2400 mm.	1			●		●
	KH.AA	Non-handed external access handle. Support and handle in black polished zamak, square spindle and crinkle washer in galvanized steel, 2 spacers and screw cup in black nylon, 1 socket head cap screw M6x16 and 2 countersunk head screws M5x70 in galvanized steel.	1					●
	KH.BB	Non-handed external access handle with safety cylinder. Support and handle in black polished zamak, brass cylinder with 3 nickel-plated keys, square spindle and crinkle washer in galvanized steel, 2 spacers and screw cup in black nylon, 1 socket head cap screw M6x16 and 2 countersunk head screws M5x70 in galvanized steel.	1					●

PURSO OY profile suitability table

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	KH.BBU	Like KH.BB but mit 3 keys (same code).	1					●
	KH.C	Non-handed external access handle with european-shaped safety cylinder. Support and handle in black polished zamak, brass cylinder with 3 nickel-plated keys, square spindle and crinkle washer in galvanized steel, 2 spacers and screw cup in black nylon, 1 socket head cap screw M6x16 and 2 countersunk head screws M5x70 in galvanized steel.	1					●
	KH.CS	Like KH.C but without cylinder.	1					●
	KH.CU	Like KH.C but mit 3 keys (same code).	1					●
	KH.E	Non-handed external access handle with safety cylinder. Support and handle in black polished zamak, brass cylinder with 3 nickel-plated keys, square spindle and crinkle washer in galvanized steel, 2 spacers and screw cup in black nylon, 1 socket head cap screw M6x16 and 2 countersunk head screws M5x70 in galvanized steel.	1					●
	KH.F	Non-handed third locking point, support in black polished aluminium, latch in nickel-plated zamak and pre-assembled self-lubricating plastic pad, fixing counterplate in galvanized steel, 2 keepers in black polished zamak, nylon cover ledge, 2 cap screws Ø 4,2x13, 4 countersunk head screws Ø 4,2x13, 4 countersunk head screws M4x30 in black galvanized steel.	1			●		●
	KH.G	Electrical keeper for art. KH in black polished aluminium; base and 4 screws in galvanized steel, spacer in black nylon. Electrical feed: 12 V CC - 15 W.	1			●		●
	KH.T	Intermediate support in zamak, die-cast metal and galvanized steel, 4 countersunk head screws Ø 4,2x13 and 4 countersunk head screws M4x30 in black galvanized steel.	1			●		●
	KH.TS	Main support for art. KH, but without counterplate, 4 countersunk head screws M4x30 in black galvanized steel.	1			●		●
	Q7.1/25	ARNO Tubular handle in polished aluminium.	4	1013, 3003, 6005, 8017, 9005, 9010, C, SILV		●		●
	Q7.1/35	ARNO Like Q7.1/25 but measure /35.	4	1013, 3003, 6005, 8017, 8019, 9005, 9010, B.SA, C, SILV		●		●

	Code	DESCRIPTION	PCS.	FINISHES	LK73	LK73 Porte	P50	P50 Porte
	Q7.2/25	PIAVE Tubular handle in polished aluminium.	4	1013, 3003, 6005, 8017, 9005, 9010, C		●		●
	Q7.2/35	PIAVE Like Q7.2/25 but measure /35.	4	1013, 3003, 6005, 8017, 9005, 9010, C		●		●
	Q7.A	Attachment for single tubular handle in galvanized steel, zamak and nylon, 6 countersunk head screws Ø 3,9x16 and 2 hex cap screws M8x30 in galvanized steel.	8			●		●
	Q7.B	Attachment for double tubular handle in galvanized steel, zamak and nylon. For door profiles with section from 30 to 60 mm.	4					●



Purso Oy
Alumiinitie 1
FI-37200 Siuro - Finland

Tel. +358 (0)3 3404 111
Fax +358 (0)3 3404 310

SAVIO S.p.A.

Via Torino, 25 (s.s. 25) - 10050 Chiusa S. Michele (TO) - Italy
Tel. +39 011 9643464 - Fax +39 011 9643474
e-mail: export@savio.it - www.savio.it