

# SKG-IKOB PRODUCTCERTIFICATE 479.472.01

Date of issue: 03-07-2019



## Certificate holder

SAVIO THESAN S.p.A.  
Via Torino 25  
I-10050 Chiusa di San Michele  
T: +39 011 964 3464  
E: info@savio.it  
I: www.savio.it



## Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

### tilt and turn hardware with window handle

delivered under logo / brand:

### SAVIO

delivered under type- and / or article number:

### SKG RIBANTA INCANTO+ (double) SKG RIBANTA 5

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
info@skgikob.nl  
www.skgikob.nl

# SKG-IKOB PRODUCTCERTIFICATE

SAVIO THESAN S.p.A.  
Number: 479.472.01

page 2 of 2

## 1. PRODUCT

tilt and turn hardware with window handle

## PRODUCT TYPE

multipoint bolt

## 2. TECHNICAL SPECIFICATION

Operating:	Mechanical operation
Construction:	1 operator mechanism with minimum 4 bolts / keeperplates
System:	by lockable SAVIO window handle
Material:	rods: aluminium anodised; hook/ keeper plates: stainless steel casting
Dimension:	rods: various length x19x3 mm; keeperplate: 44x24x13,5 mm; hook: 50x15,5x13 mm
Fixing:	mechanism/ keeperplate: slide into euro-groove; hook: unilaterally clamped and self-forming screw M5x18 mm
Intended use:	metal, window-inward-opening in combination with lockable SAVIO window handle

## 3. DELIVERY

The delivery includes an installation instruction:

(Tilt)/ turn: 89011139 - REV.0 - 127091 , 89011217 - REV.0 - 131052

Outwards turning single leaf: not rel.

Inwards turning double leaf: 89011584 - REV.0 - 103026

Outwards turning double leaf: not rel.

Tilt&slide: not rel.

Folding element: not rel.

## 4. PERFORMANCES

A tilt and turn hardware with window handle according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this tilt and turn hardware, with window handle is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this tilt and turn hardware, with window handle is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).